



ECOGEN S9041HO/TC - 13W

High output dimmable IP44 LED downlight with selectable CCT

Application

Ideal for any residential or commercial interior space

Design Specifications


- Selectable CCT 3000K/4200K/5700K
- Durable die-cast aluminium body profile
- Stylish white powder coat finish or satin nickel
- Colour trim options: (black ring S9041 BK RING), (satin nickel S9041 SN RING), (silver ring S9041 SL RING)
- Remote constant current trailing edge dimmable LED driver, with flex and plug
- High efficiency LED optics, opal polycarbonate diffuser.

Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge, optional 1-10V, DALI / DSI**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9041HO/TC/WH	240	13	1040/1170/1105	3000/4200/5700	90


Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	80	WHITE	92	103	40(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions



Dimensions



THE SFI SYSTEM ELIMINATES LED FLICKERING.

**SIMPLY
MATCH THE
ECOGEN SFI
DOWNLIGHT
WITH THIS
SDD400SFI
DIMMER.**



**DIM with
FLICKER
CONTROL**

For related
products
please
scan me

