



Copper Crimp Reducing Links

Our range of Copper Lugs/Links and Reducing Links complies to Australian & New Zealand standard AS/NZS4325 Part 1:1995 as well as International Standards.

Large End Dimensions Small End

Part No	Description	A	B	ID	C	ID
CCLR16-6	Crimp Reducing 16.0mm ² -6.0mm ²	55.0	27.0	5.5	28.0	3.7
CCLR16-10	Crimp Reducing 16.0mm ² -10.0mm ²	55.0	27.0	5.5	28.0	4.5
CCLR25-6	Crimp Reducing 25.0mm ² -6.0mm ²	56.0	27.0	7.2	29.0	3.7
CCLR25-10	Crimp Reducing 25.0mm ² -10.0mm ²	56.0	27.0	7.2	29.0	4.5
CCLR25-16	Crimp Reducing 25.0mm ² -16.0mm ²	56.0	56.0	7.2	29.0	5.5
CCLR35-10	Crimp Reducing 35.0mm ² -10.0mm ²	56.0	56.0	8.5	29.0	4.5
CCLR35-16	Crimp Reducing 35.0mm ² -16.0mm ²	56.0	56.0	8.5	29.0	5.5
CCLR35-25	Crimp Reducing 35.0mm ² -25.0mm ²	56.0	56.0	8.5	28.0	7.2
CCLR50-16	Crimp Reducing 50.0mm ² -16.0mm ²	58.0	58.0	9.5	30.0	5.5
CCLR50-25	Crimp Reducing 50.0mm ² -25.0mm ²	58.0	58.0	9.5	30.0	7.2
CCLR50-35	Crimp Reducing 50.0mm ² -35.0mm ²	58.0	58.0	9.5	30.0	8.5
CCLR70-25	Crimp Reducing 70.0mm ² -25.0mm ²	58.0	58.0	11.0	30.0	7.2
CCLR70-35	Crimp Reducing 70.0mm ² -35.0mm ²	58.0	58.0	11.0	30.0	8.5
CCLR70-50	Crimp Reducing 70.0mm ² -50.0mm ²	58.0	58.0	11.0	30.0	9.5
CCLR95-35	Crimp Reducing 95.0mm ² -35.0mm ²	75.0	75.0	13.5	46.0	8.5
CCLR95-50	Crimp Reducing 95.0mm ² -50.0mm ²	75.0	75.0	13.5	46.0	9.5
CCLR95-70	Crimp Reducing 95.0mm ² -70.0mm ²	75.0	75.0	13.5	46.0	11.0
CCLR120-50	Crimp Reducing 120.0mm ² -50.0mm ²	75.0	75.0	15.0	46.0	9.5
CCLR120-70	Crimp Reducing 120.0mm ² -70.0mm ²	75.0	75.0	15.0	46.0	11.0
CCLR120-95	Crimp Reducing 120.0mm ² -95.0mm ²	88.0	88.0	15.0	44.0	13.5
CCLR150-70	Crimp Reducing 150.0mm ² -70.0mm ²	77.0	77.0	16.5	48.0	11.0
CCLR150-95	Crimp Reducing 150.0mm ² -95.0mm ²	90.0	90.0	16.5	46.0	13.5
CCLR150-120	Crimp Reducing 150.0mm ² -120.0mm ²	90.0	90.0	16.5	46.0	15.0

