

## PVC CORRUGATED CONDUIT HEAVY DUTY ORANGE

Tripac Heavy Duty Electrical Corrugated Conduit is a high-quality polyvinyl chloride (PVC) conduit designed to provide excellent flexibility, strength and protection for your wiring and cables. It is specifically engineered to meet the demands of under-ground electrical applications, offering superior resistance to impact, water, weather, chemicals, and corrosive environments.



### FEATURES & BENEFITS

- High-quality PVC construction ensures durability and longevity.
- Excellent flexibility allows for easy installation in complex setups.
- Provides superior protection for electrical cables and wiring.
- UV stabilized to withstand prolonged exposure to sunlight and outdoor conditions.
- Non-flame propagating for enhanced safety.
- Manufactured in accordance with AS/NZS 61386.1:2015 AMD 1:2019 (General Requirements) and AS/NZS 61386.23:2022 (Flexible Conduits).
- BEP certified for environmental compliance.
- Compression strength exceeding 1250N.

### PRODUCT SPECIFICATIONS

- **Type:** Heavy Duty (HD)
- **Colour:** Orange
- **Material:** Polyvinyl Chloride (PVC)
- **Temperature Range:** -5°C to 60°C
- **UV Resistance:** Yes
- **Flame Retardant:** Yes
- **Compression Strength:** >1250N
- **Conforms to:** Manufactured in accordance with AS/NZS 61386.1:2015 AMD 1:2019 (General Requirements) and AS/NZS 61386.23:2022 (Flexible Conduits)

### ORDERING INFORMATION

PART NO.	DESCRIPTION
CCO2010	CORRUGATED CONDUIT ORANGE 20MM X 10M
CCO2025	CORRUGATED CONDUIT ORANGE 20MM X 25M
CCO2050	CORRUGATED CONDUIT ORANGE 20MM X 50M
CCO2510	CORRUGATED CONDUIT ORANGE 25MM X 10M
CCO2525	CORRUGATED CONDUIT ORANGE 25MM X 25M
CCO2550	CORRUGATED CONDUIT ORANGE 25MM X 50M
CCO3210	CORRUGATED CONDUIT ORANGE 32MM X 10M
CCO3225	CORRUGATED CONDUIT ORANGE 32MM X 25M
CCO4010	CORRUGATED CONDUIT ORANGE 40MM X 10M
CCO4025	CORRUGATED CONDUIT ORANGE 40MM X 25M
CCO5010	CORRUGATED CONDUIT ORANGE 50MM X 10M
CCO5025	CORRUGATED CONDUIT ORANGE 50MM X 25M



Mercury & Lead Free



UV Stabilised



Non-Flame Propagating



Operating Temperature -5°C to 60°C



Conforms to AS/NZS 2053.5:2001



>1250N Compression Strength



MKT305

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.