


Perforated hot-dip galvanized half saddles Ø 32 mm (x 50)



Characteristics

Ø d (mm) : 32  
 Ø1 (mm) : 6.5  
 H (mm) : 32  
 L (mm) : 68.5  
 L1 (mm) : 35  
 W (mm) : 25.4  
 Thickness (mm) : 1.2  
 Quantity per box : 50  
 Selling unit : EACH

Benefits

- Reinforced for better support.

GENERAL INFORMATION

Technical details

Hot-dip galvanized steel.  
 Coating: > 45 µm.

Advice

Make sure that the fastening is suitable for the surface to which it is to be attached.

Application(s)

For securing and fastening electrical cables, tubes and ducts to various types of surfaces.  
 For indoor and outdoor use.  
 Fastens with screws (requires drilling).

LOGISTIC INFORMATION

Packaging



Solid cardboard box

Height (cm) : 12.3  
 Length (cm) : 16.5  
 Depth (cm) : 12.3  
 Net weight (kg) : 1.34  
 Gross weight (kg) : 1.44



Outer package 1



Carton box

Height (cm) : 14  
 Length (cm) : 62  
 Depth (cm) : 35  
 Net weight (kg) : 15  
 Gross weight (kg) : 16

x 10.00



Outer package 2



Pallet

Height (cm) : 130  
 Length (cm) : 120  
 Depth (cm) : 80  
 Net weight (kg) : 512  
 Gross weight (kg) : 522

x 320.00

