



Cable ties for outdoor use (UV-resistant)

T-Series in PA66W/UV black

These inside serrated cable ties are made of UV-resistant Polyamide 6.6 (PA66W) and thus suitable for outdoor applications. UV stabilised cable ties resist UV radiation for a considerably longer period compared to standard PA66 cable ties. They can easily be used for bundling and securing cables, pipes and hoses especially in outdoor areas.


Features and benefits

- UV-resistant black cable tie available in a wide range of sizes
- Made from 100 % high quality plastic, allows for good recycling
- Inside serration for a strong hold onto bundles
- Easy application either manually or with a processing tool
- Simple to insert due to bent tail




UV-resistant T-Series cable ties (PA66W/UV).

Material information at HellermannTyton.com.au/materialoverview



T-Series



T250-series


TYPE	Width (W)	Length (L)	Bundle Ø max.	N	Material	Colour	Pack Cont.	Tools	Local Part No.	Art.-No.
T18R	2.5	100.0	22.0	80	PA66W	Black (BK)	100 pcs.	2;5;23;25	T18RBK/W	111-01960
	2.5	100.0	22.0	80	PA66W	Black (BK)	1000 pcs.	2;5;23;25	T18RBK/W-1000	111-01867
T18I	2.5	145.0	35.0	80	PA66W	Black (BK)	100 pcs.	2;5;23;25	T18IBK/W	111-02360
T18L	2.5	205.0	50.0	80	PA66W	Black (BK)	100 pcs.	2;5;23;25	T18LBK/W	111-02160
T25L	2.8	240.0	65.0	110	PA66W	Black (BK)	100 pcs.	2;5;23;25	T25LBK/W	111-02560
T30R	3.5	150.0	35.0	135	PA66W	Black (BK)	100 pcs.	2;5;23;25	T30RBK/W	111-03260
	3.5	150.0	35.0	135	PA66W	Black (BK)	1000 pcs.	2;5;23;25	T30RBK/W-1000	111-03280
T30L	3.5	198.0	50.0	135	PA66W	Black (BK)	100 pcs.	2;5;23;25	T30LBK/W	111-00947
	3.5	198.0	50.0	135	PA66W	Black (BK)	1000 pcs.	2;5;23;25	T30LBK/W-1000	111-03461
T30LL	3.5	290.0	80.0	135	PA66W	Black (BK)	100 pcs.	2;5;23;25	T30LLBK/W	111-03580
T40R	4.0	180.0	40.0	180	PA66W	Black (BK)	100 pcs.	2;5;23;25	T40RBK/W	111-03860
T50S	4.6	150.0	35.0	225	PA66W	Black (BK)	100 pcs.	2;5;7;23;25	T50SBK/W	111-05860
T50R	4.6	200.0	50.0	225	PA66W	Black (BK)	1000 pcs.	2;5;7;9;23;25	T50RBK/W-1000	111-00984
	4.6	202.0	50.0	225	PA66W	Black (BK)	100 pcs.	2;5;7;9;23;25	T50RBK/W	111-04860
T50I	4.6	300.0	85.0	225	PA66W	Black (BK)	1000 pcs.	2;5;7;9;23;25	T50IBK/W-1000	111-05263
	4.6	305.0	80.0	225	PA66W	Black (BK)	100 pcs.	2;5;7;9;23;25	T50IBK/W	111-00952
T50L	4.6	390.0	110.0	225	PA66W	Black (BK)	100 pcs.	2;5;7;9;23;25	T50LBK/W	111-05710
	4.6	390.0	110.0	225	PA66W	Black (BK)	1000 pcs.	2;5;7;9;23;25	T50LBK/W-1000	111-01610
T80R	4.7	205.0	55.0	355	PA66W	Black (BK)	100 pcs.	2;5;7;23;25	T80RBK/W	111-05060
T80I	4.7	305.0	85.0	355	PA66W	Black (BK)	100 pcs.	2;5;7;23;25	T80IBK/W	111-08290
T80L	4.7	390.0	110.0	355	PA66W	Black (BK)	100 pcs.	2;5;7;23;25	T80LBK/W	111-05460

Recommended Tools: 2=MK20, 5=EVO7i, 7=EVO9i, 9=EVO9iHT, 23=TG009, 25=EVOcut. For more information on toolings please go to www.HellermannTyton.com.au/application-tooling.

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available. N = Minimum Loop Tensile Strength for Cable Ties (newton)



Please note: Some or all of the products listed here have these approvals, or have one or more sustainable attributes. Please see our website for the latest details.



TYPE	Width (W)	Length (L)	Bundle Ø max.		Material	Colour	Pack Cont.	Tools	Local Part No.	Art.-No.
T120I	7.6	300.0	80.0	535	PA66W	Black (BK)	100 pcs.	7;9;23;25	T120IBK/W	111-12160
T150R(H)	7.6	365.0	100.0	670	PA66W	Black (BK)	100 pcs.	7;9;23;25	T150RBK/W	111-14860
T120R	7.6	388.0	100.0	535	PA66W	Black (BK)	100 pcs.	7;9;23;25	T120RBK/W	111-00944
T120M	7.6	460.0	125.0	535	PA66	Black (BK)	100 pcs.	7;9;23;25	T120MBK	111-12610
T120XM	7.6	600.0	175.0	535	PA66	Black (BK)	50 pcs.	7;9;23;25	T120XMBK	111-12701
T120L	7.6	760.0	225.0	535	PA66W	Black (BK)	50 pcs.	7;9;23;25	T120LBK/W	111-12460
T150M	8.9	530.0	150.0	780	PA66W	Black (BK)	25 pcs.	7;9;23	T150MBK/W	111-15660
T150L	8.9	820.0	245.0	780	PA66W	Black (BK)	25 pcs.	7;9;23	T150LBK/W	111-15460
T150LL	8.9	925.0	274.3	780	PA66W	Black (BK)	25 pcs.	7;9;23	T150LLBK/W	111-15704
T150XL	8.9	1095.0	330.0	780	PA66W	Black (BK)	25 pcs.	7;9;23	T150XLBK/W	111-15502
T150XLL	8.9	1325.0	405.0	780	PA66	Black (BK)	25 pcs.	7;9;23	T150XLLBK	111-15300
T250R	12.4	515.0	125.0	1115	PA66	Black (BK)	25 pcs.	7;9	T250RBK	111-24801
T250M	12.4	565.3	150.0	1115	PA66	Black (BK)	25 pcs.	7;9	T250MBK	111-25001
T250I	12.4	730.0	203.0	1115	PA66	Black (BK)	25 pcs.	7;9	T250IBK	111-00507
T250L	12.4	880.0	254.0	1115	PA66	Black (BK)	25 pcs.	7;9	T250LBK	111-24601

Recommended Tools: 2=MK20, 5=EVO7i, 7=EVO9i, 9=EVO9iHT, 23=TG009, 25=EVOcut. For more information on toolings please go to www.HellermannTyton.com.au/application-tooling.

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available. N = Minimum Loop Tensile Strength for Cable Ties (newton)



Please note: Some or all of the products listed here have these approvals, or have one or more sustainable attributes. Please see our website for the latest details.