40RSM3

Iconic - 4position rotary switch mechanism labelled 0-1-2-3 10A 250V



Main

Range	Clipsal Iconic
Product or component type	Switch mechanism
Device presentation	Mechanism
Provided equipment	Switch Knob Carrier labelled with switch position
Device application	Small appliances
Fixing mode	Locking bar
Colour tint	Vivid white (VW) Vivid white (VW) Anthracite (AN) Cool grey (CY) Warm grey (WY)
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Rated current	10 A - 250 V AC, 50 Hz

Complementary

oompicmentary		
Switch function	4 positions	
Control type	Rotary	
Actuator	Rotary	
Marking	0-1-2-3	
Surface finish	Matt	
Surface treatment	Untreated	
Ambient air temperature for storage	060 °C	
Motor M-rating AS3133	M40	
Load type	Inductive Motor	
Dielectric strength	40000 V	
Ambient air temperature for operation	045 °C	
Relative humidity	1095 %	
Electrical durability	20000 cycles, conforming to AS/NZS 60669	
Connections - terminals	4 x screw terminals	
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)	
Clamping connection capacity	1.5 mm² (stranded) 1.5 mm² (flexible) 1.5 mm² (rigid)	
Wire stripping length	10 mm	_
Material	Housing : PC (polycarbonate) Housing : PC (polycarbonate) Housing : PA66 Knob : PC (polycarbonate) Knob cap : ABS (acrylonitrile butadiene-styrene)	
Height	23 mm	
Width	23 mm	
Depth	50 mm	
Product weight	0.02 kg	,

Environment



Offer Sustainability

Sustainable offer status	Not Green Premium product
REACh	Reference not containing SVHC above the threshold

