ISOSW440PROLB

NHP ISO Surface Switch, 4 Pole 40A 500V AC, w/o Base, Resistant Orange





Component type	Switch disconnector
Range	ISO
Model	N/A
Product status	Existing

NHP's ISO™ (Industrial Strength Options) diverse range of plugs, sockets and switches offer choice and excellent value. With over 400 options covering 10 to 50A in 3, 4 and 5 pin configurations, the range is suited for domestic, commercial and industrial applications. IP66 and UV stabilised as standard, with chemical resistant versions available. Available from an NHP recognised wholesale stockist.

ELECTRICAL	Rated operating voltage Ue	500 V
	Rated permanent current lu	40.0 A
	Number of poles	4
	Frequency	50 Hz
	Rated operation current le at AC-23, 500 V	40.0 A
	Rated operating voltage	500 V
CONSTRUCTION	Material housing	Plastic
	Colour control element	Grey
	Degree of protection (IP), front side	IP66
	Degree of protection (NEMA)	4X
	Version as reversing switch	No
	Suitable for floor mounting	No
MECHANICAL	Padlock locking	Yes
DIMENSIONS	Height	95.0 mm
	Width	95.0 mm
	Depth	54.0 mm
	Connectable conductor cross section	1.5 - 6 mm²