

40CSFM

Iconic - 4-position rotary switch mechanism plus capacitor 10A 250V 4colour



Main

Range	Clipsal Iconic
Product or component type	Switch mechanism
Device presentation	Mechanism
Provided equipment	Capacitor Switch Knob
Device application	Fan speed controller
Fixing mode	Locking bar
Colour tint	Vivid white (VW) Vivid white (VW) Anthracite (AN) Cool grey (CY) Warm grey (WY)
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Rated current	10 A - 250 V AC, 50 Hz

Complementary

Switch function	4 positions
Control type	Rotary
Actuator	Rotary
Marking	0 - 1 - 2 - 3
Surface finish	Matt
Surface treatment	Untreated
Ambient air temperature for storage	0...60 °C
Motor M-rating AS3133	M40
Load type	Inductive
Dielectric strength	20000 V
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Electrical durability	20000 cycles, conforming to AS/NZS 60669
Connections - terminals	4 x screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	1.5 mm ² (stranded) 1.5 mm ² (flexible) 1.5 mm ² (rigid)
Wire stripping length	10 mm
Material	Housing : PC (polycarbonate) Housing : PC (polycarbonate) Housing : PA66 Knob : PC (polycarbonate) Knob cap : ABS (acrylonitrile butadiene-styrene)
Height	23 mm
Width	23 mm
Depth	51 mm
Product weight	0.042 kg

Environment

