

Catalogue No: **UWP30RSEXXX**

MONITORING AND GATEWAY CONTROL 15-24V DC ETHERNET USB RS485

Energy Management and Building Automation > Energy Management and Metering > Energy Monitoring Software > Carlo Gavazzi Monitoring Devices > UWP 3.0 - Energy Monitoring Platform and BACnet/IP gateway > UWP 3.0 Controller



UWP 3.0 Monitoring and gateway control 15-24V DC Auxiliary with Modbus RTU, Modbus TCP and USB

- Compact 2-DIN footprint
- Simple and quick to configure
- 4GB Data logging for interval time date stamping of realtime variables
- Compatible with a wide range of energy meters
- Customisable monitoring dashboard and reporting available through WebApp on any browser, smartphone or tablet

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Function(s)	EMS, Gateway type
Embedded Web Server	Yes
Number of Meters	≥64 (Meter type and cable distant dependent)
Maximum Datapoints	5000
Real Time Clock	Integrated
Remote Monitoring	Yes Y/N
Alarm Function	Yes
Communications Protocols	BACNet/IP Ethernet TCP/IP Modbus-TCP/IP Modbus-RTU FTP FTPS HTTP HTTPS RS-485 NTP SNTP
Software additional modules	EM ² or InfoSyte for MultiSite Applications
Power Consumption	≤ 5W
Supply Voltage Type	15-24 VDC ± 20%



Catalogue No: **UWP30RSEXXX**

MONITORING AND GATEWAY CONTROL 15-24V DC ETHERNET USB RS485

Energy Management and Building Automation > Energy Management and Metering > Energy Monitoring Software > Carlo Gavazzi Monitoring Devices > UWP 3.0 - Energy Monitoring Platform and BACnet/IP gateway > UWP 3.0 Controller



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -