

Product No: CE4T-10R-01

ABB E/STOP 40mm NON-ILLUMINATED COMPACT TWIST
RELEASE CE4T-10R-01

FEATURES



- Space-saving and easy to integrate into machinery setups
- Twist-release mechanism allows for fast deactivation during emergencies
- Built to withstand harsh environments
- Easy integration

General Information	
Brand	ABB
Enclosure Type (NEMA)	Type1, Type12, Type13, Type3R, Type4, Type4X
Product Type	Emergency Stop
Technical Attributes	
Connecting Capacity	Flexible with Ferrule 1/2 x 0.5 – 1.5 mm² Flexible with Insulated Ferrule 1/2 x 0.5 – 1.5mm² Flexible 1/2 x 0.5 – 1.5mm² Solid 1/2 x 0.5 – 1.5mm²
Connection Type	Screw Clamp
Function	Maintained
No. of Normally-closed Contacts	1
Power Loss (W)	Maximum 2.5W
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	300
Rated Operational Current AC-15 240V (A)	1
Rated Operational Current DC-13 125V (A)	0.2
Rated Operational Current DC-13 24V (A)	0.3
Rated Operational Voltage (V)	24 – 300
Sub-Function	Twist Release
Terminal Type	Screw



Tightening Torque (Nm)	0.8
------------------------	-----

Wire Stripping Length (mm)	6
----------------------------	---

Physical Attributes

Actuator Type	Mushroom 40mm
---------------	---------------

Ambient Temperature Range (°C)	-25 to 70
--------------------------------	-----------

Colour	Red
--------	-----

Storage Temperature Range (°C)	-40 to 85
--------------------------------	-----------

Dimensions

Dimensions (mm)	40W x 40H x 73D
-----------------	-----------------

Weight (kg)	0.034
-------------	-------

Protection & Standards

Degree of Protection	Front: IP66, IP67, IP69K; Terminals: IP20
----------------------	---

Pollution Degree	3
------------------	---

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------