



UFO SHB23MP200TC - 100/150/200

Dimmable, IP65 LED UFO highbay with selectable CCT and power.

Application

Super low profile dimmable LED highbay, ideal for commercial or industrial warehouse environments

Design Specifications

- Integral selectable power 100 / 150 or 200 watts
- Integral selectable CCT 3000, 4000 or 5000K
- Robust, low profile die-cast aluminium IP65/IK08 body profile.
- High efficiency LED optics, with an impressive > 140lm/W optical performance at 150W/4000K, CRI > 80, 90 degree beam distribution, polycarbonate lens
- Integral 1-10V dimmable LED driver, complete with flex and plug for easy installation, optional inline DALI (1) addressable signal converter, optional plug and play corridorSTANDBY sensor
- Power/lumen settings at;
3000K : 100W/13000lm, 150W/18000lm, 200W/22000lm,
4000K : 100W/14500lm, 150W/21000lm, 200W/26000lm,
5000K : 100W/14000lm, 150W/19500lm, 200W/24000lm.

Performance

- Dimmable - **YES**
- Dimmer Type - **1-10V, optional SAL DALI (1) addressable signal converter**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	Beam Angle (°)	CCT (K)
	SHB23MP200TC	240	100/150/200	14500/21000/26000	90	3000/4000/5000
	SHB23MP/CS					
	SHB25HES/RC					
	SHB23SE/PPR					
	SHB23MP200PLB					
	LM-DALI010B					

CRI	Body Colour	Diameter (mm)	Dim (mm)	Mass (kg)	IPART
80	BLACK	300	300(W) x 192(H)	2.78	YES
	CORRIDOR SENSOR			0.04	
	REMOTE CONTROL				N/A
	PRISMATIC REFLECTOR			0.4	N/A
	BLACK				N/A
	DALI SIGNAL CONVERTER			0.06	

Note: (1) 1-10V dimming does not provide 100% OFF dimming function.

Note: (2) lumens (lm) shown are displayed at the **4000K 100/150/200W power setting**

Note: (3) Sensor default settings: Sensitivity=100%, Hold Time=30mins, StandBy power=30%, StandBy time 30mins, Daylight Threshold=disabled

Note: (4) Sensor and dimming functions cannot be operated simultaneously.

Note: (5) Remote control and sensor function height max 10M.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

PDF Prepared: 19.3.2025 10:04am
Last page update: Nov 2023
© Copyright SAL - All Rights Reserved