



OPAL SO3700/TC/DP2 - 8/30W

LED Oyster 8 to 30 watt with selectable colour temperature, dual power and dimming options

Application

A perfect choice for apartments or commercial spaces


Design Specifications

- Selectable colour temperature with the integral DIP switch 3000K / 4000K / 6000K
- Durable powder coated steel body profile with a high performance opal PMMA diffuser
- High efficiency SMD LED chips, CRI > 80
- Integral constant current LED driver, refer Dimmable model numbers
- Integral dual power selection
- Two versatile profile sizes 8/16 or 15/30 watt

Performance

Dimmable - **YES**

Dimmer Type - **Trailing edge**



Technical Specification

Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	CRI	Dimmable
SO3700/30TC/DP2	240	8/16	1100/1400/1200	3000/4000/6000	80	NO
SO3700/40TC/DP2	240	15/30	2350/2800/2400	3000/4000/6000	80	NO
SO3700/30TC/DPD	240	8/16	1100/1400/1200	3000/4000/6000	80	YES
SO3700/40TC/DPD	240	15/30	2350/2800/2400	3000/4000/6000	80	YES

Model No.	Beam Angle (°)	Body Colour	Diameter (mm)	Dim (mm)	iPART
SO3700/30TC/DP2	120	White	310	78(H)	YES
SO3700/40TC/DP2	120	White	390	102(H)	YES
SO3700/30TC/DPD	120	White	310	100(H)	
SO3700/40TC/DPD	120	White	390	112(H)	

Note: Lumens (lm) values shown are at full power rating

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

PIXIE AMBIENCE, CHANGE YOUR STYLE.



PIXIE AMBIENCE GPO SMART SOCKET
SPO23/BTAM



For more
information
please
scan me

