

CAPACITY			2.0kW	2.5kW	2.5kW (Cool Only)	3.5kW	3.5kW (Cool Only)	5.0kW	5.0kW (Cool Only)	
Indoor			SRK20ZSA-W / DXK06ZSA-W	SRK25ZSA-W / DXK09ZSA-W	SRK10YSA-W	SRK35ZSA-W / DXK12ZSA-W	SRK13YSA-W	SRK50ZSA-W / DXK18ZSA-W	SRK18YSA-W	
Outdoor			SRC20ZSA-W / DXC06ZSA-W	SRC25ZSA-W / DXC09ZSA-W	SRC10YSA-W	SRC35ZSA-W / DXC12ZSA-	SRC13YSA-W	SRC50ZSA-W / DXC18ZSA-W	SRC18YSA-W	
Power Source (Outdoor Unit)			W 1 Phase 240V 50Hz							
*Operation Data	Nominal Capacity (Range)	Cooling T1	2.0 (0.9-3.0)	2.5 (0.9-3.5)	2.5 (0.9-3.5)	3.5 (0.9-4.4)	3.5 (0.9-4.4)	5.0 (1.2-5.5)	5.0 (1.2-5.5)	
		Heating H1	2.7 (1.0-4.2)	3.2 (0.9-5.2)	N/A	3.7 (0.9-5.4)	N/A	5.8 (1.2-6.6)	N/A	
		Heating H2	3.2	3.95	N/A	4.0	N/A	5.2	N/A	
	Power Consumption	Cooling T1	0.41 (0.18-0.81)	0.51 (0.18-0.88)	0.51 (0.18-0.88)	0.82 (0.18-1.27)	0.82 (0.18-1.27)	1.39 (0.27-1.86)	1.39 (0.27-1.86)	
		Heating H1	0.56 (0.20-1.12)	0.65 (0.21-1.43)	N/A	0.81 (0.21-1.44)	N/A	1.49 (0.26-1.97)	N/A	
	Maximum Power Consumption		1.65	1.65	1.65	1.65	1.65	2.68	2.68	
	Running Current	Cooling T1	2.1	2.5	2.5	3.7	3.7	5.9	5.9	
		Heating H1	2.7	3.0	N/A	3.7	N/A	6.3	N/A	
	Inrush Current, Maximum Current		2.8, 9.0	3.2, 9.0	2.6, 9.0	3.9, 9.0	3.9, 9.0	5.0, 14.5	5.0, 14.5	
	EER	Cooling T1	4.88	4.90	4.90	4.27	4.27	3.60	3.60	
	COP	Heating H1	4.82	4.92	N/A	4.57	N/A	3.89	N/A	
	Sound Power Level (JIS C9612)		Outdoor	56	58	58	62	62	61	61
	Sound Pressure Level (JIS C9612)	Indoor	35-27-22-19	40-31-22-19	39-31-22-19	43-34-27-19	43-34-27-19	43-36-28-22	43-36-28-22	
Outdoor		44	45	45	50	49	49	47		
Energy Label (GEMS 2019)	Hot	Cooling	★★★★★(4)	★★★★★(4)	★★★★★(4)	★★★★(4)	★★★★(4)	★★★★★(3)	★★★★★(3)	
		Heating	★★★★★(5) ⁽³⁾	★★★★★(5) ⁽³⁾	N/A ⁽⁵⁾	★★★★★(3)	N/A	★★★★★(5) ⁽³⁾	N/A ⁽⁵⁾	
	Average	Cooling	★★★★★(5)	★★★★★(5) ⁽³⁾	★★★★★(3)	★★★★★(5) ⁽³⁾	★★★★★(3)	★★★★★(5)	★★★★★(5)	
		Heating	★★★★★(4) ⁽³⁾	★★★★★(5) ⁽³⁾	N/A ⁽⁵⁾	★★★★★(5) ⁽³⁾	N/A ⁽⁵⁾	★★★★★(3) ⁽²⁾	N/A ⁽³⁾	
	Cold	Cooling	★★★★★(5)	★★★★★(3)	★★★★★(3)	★★★★★(3)	★★★★★(3)	★★★★★(5)	★★★★★(5)	
		Heating	★★★★★(4) ⁽³⁾	★★★★★(5) ⁽³⁾	N/A ⁽⁵⁾	★★★★★(5) ⁽²⁾	N/A ⁽⁵⁾	★★★★★(3)	N/A ⁽³⁾	
External dimensions (HXWxD)		Indoor	290x870x230	290x870x230	290x870x230	290x870 ⁽⁵⁾ x230	290x870x230	290x870 ⁽²⁾ x230	290x870x230	
		Outdoor	540x780(+62)x290	540x780(+62)x290	540x780(+62)x290	540x780(+62)x290	540x780(+62)x290	640x800(+71)x290	640x800(+71)x290	
Net weight		Indoor	9.5	10	10	10	10	10	10	
		Outdoor	33	36	33.5	36	33.5	43.5	40	
Airflow		Cooling (Indoor)	165-127-93-83	182-140-88-78	182-140-88-78	205-152-117-78	205-152-117-78	213-175-113-93	213-175-113-93	
		Heating (Indoor)	190-142-108-93	237-182-110-88	N/A	250-193-117-88	N/A	253-198-152-113	N/A	
Installation Data	Refrigerant (Type, Amount, Pre-charge Length)	Quantity	(R32) 0.58	(R32) 0.78	(R32) 0.75	(R32) 0.78	(R32) 0.75	(R32) 1.05	(R32) 1.05	
		Pre-Charged to Pipe	15	15	15	15	15	15	15	
	Refrigerant Piping	Liquid line	Ø6.35	Ø6.35	Ø6.35	Ø6.35	Ø6.35	Ø6.35	Ø6.35	
		Gas line	Ø9.52	Ø9.52	Ø9.52	Ø9.52	Ø9.52	Ø12.7	Ø12.7	
	Connection Method		Flare connection							
Maximum Pipe Length (One Way)		20							25	
Max Vertical Height Diff. Between O.U. and I.U.		10 (O.U. above I.U.) / 10 (O.U. below I.U.)							15 (O.U. above I.U.) / 15 (O.U. below I.U.)	
Standard accessories			Allergen Clear & Photocatalytic Washable Deodorizing Filter		Enzyme Filter & Photocatalytic Washable Deodorizing Filter	Allergen Clear & Photocatalytic Washable Deodorizing Filter	Enzyme Filter & Photocatalytic Washable Deodorizing Filter	Allergen Clear & Photocatalytic Washable Deodorizing Filter	Enzyme Filter & Photocatalytic Washable Deodorizing Filter	
Optional parts			Interface kit (SC-BIKN2-E) / Wi-Fi Kit							
Demand Response (AS4755)			Yes	Yes	Yes	Yes	Yes	Yes	Yes	