



# LYNK GATEWAY

EV-GATEWAY-LK

Lynk Gateway Wireless Emergency Testing and Monitoring,  
Field mount

## FEATURES

- Supports up to 64 Lynk emergency devices
- Automatic addressing of Lynk emergency devices
- 10/100 TCP/IP Ethernet compatible with standard IT switches and equipment
- Wireless mesh
- Suitable for field mounting in ceiling
- 12 years design life at max. ambient



## ORDERING INFORMATION

Order code	12803
Description	Ektor Lynk Gateway - EWAC Controller
Item Code	EV-GATEWAY-LK

## MECHANICAL

Body Material	Polycarbonate
Installation Type	Field mount
IP Rating	IP20

## ELECTRICAL

Electrical Rating	Class II
Input Frequency	50 Hz
Input voltage	230Vac
In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%	
Working Temp Range	0 to 40 °C

## COMPLIANCE

Standards	AS/NZS 61347.2.11 AS/NZS 61347.1 AS CISPR 15 AS/NZS 4268 IEC 62386-104 IEC 62386-103
-----------	---

## WARRANTY

Commercial Use Warranty	3 RTB (Total 3 Years)
-------------------------	-----------------------

## LINE DRAWINGS

EV/GATEWAY/LK

