

enLighten | Innovation in Lighting Solutions

Emergency/Corridor Luminaire



The Chamaeleon Deco 2 is an elegant, slim and versatile decorative light, that is easy to customise, with adjustable brightness and dual colour temperature switch.

Thanks to an integrated smart daylight sensor, your lights only turn on only when needed. The Chamaeleon Deco 2 is a smart light that goes into standby mode at dusk and reaches full light when motion is detected. At dawn the luminaire switches off automatically to save energy.

This versatile bulkhead comes with a dual colour switch, making it easy for you to achieve the colour temperature you need, choose from 3000K warm white or 4000K natural white. Having completely separate light circuits ensures colour consistency over the age of the fitting.

Ideal for every corridor, lobby and building exterior. It is available in emergency and nonemergency.

OPTIONS AND BENEFITS

- Emergency and non-emergency options available
- Adjustable brightness 1500/1000/700 lumens options within same fitting
- Dual colour switch with the flick of a switch choose either 3000K warm white or 4000K natural white colour tone
- 2 & 3 Step sensor dimming offers full, standby & off
- Smart daylight sensor your lights only turn on when needed
- Flicker free
- Low standby power 0.5W to 5.5W
- Expected life >60,000 @L70 delivered by high quality Samsung LEDs
- 5 year warranty

APPLICATIONS











FEATURES



















RATING







SELECTABLE BRIGHTNESS



WARRANTY



CORRIDORS

TOILETS


enLighten

Chamaeleon Deco 2

PRODUCT RANGE


Model #	Description	Lumens (Im)		Rated Power (W)	
		Full light	Standby	Full light	Standby 10%
D2-CHAM	Chamaeleon Deco 2 Standard with built-in microwave motion and daylight sensor	1,500 1,000 700	25% 10% Off	16 11 8	2
D2-CHAM-E	Chamaeleon Deco 2 Emergency with built- in microwave motion and daylight sensor	1,500 1,000 700	25% 10% Off	17 12 9	3

DIMENSIONS



Model shown: D2-CHAM

PHOTOMETRICS



Model shown: D2-CHAM

COMPLIANCE

The Chamaeleon Deco 2 series meets or exceeds all relevant standards and regulatory requirements.



For a full compliance and testing list visit www.enlighten.com.au. IES files, warranty, installation and product guides are also available for download.

Sold nationally through major electrical wholesalers.



TECHNICAL INFORMATION

Optical			
Light source	Samsung LEDs		
Lumen output	1500 (max), 1000, 700 lumens		
CRI	Ra>80		
CCT	3000K or 4000K (colour selectable		
Electrical			
Power consumption	16W Standard, 17W Emergency		
Standby light level	25%, 10% & Off		
Standby power	0.5W - 5.5W		
Operating frequency	50/60Hz		
Operating voltage range	220 - 240 V AC		
Emergency light			
Battery type	3.2V 3000mAh LiFePO4		
Discharge time	90 minutes		
Emergency classification	D40		
Environmental			
IP rating	IP44		
Impact rating	IK10		
Weight	1.3kg (standard), 1.5kg (emergency)		
Temperature range	0°C to +40°C		
Material Composition (body)	Polycarbonate (UV stabilised)		
Material Composition (diffuser)	Polycarbonate (UV stabilised)		
Expected Lifespan	>60,000 hours @ L70		
Controls			
Selectable brightness	Allows for adjustable brightness, select 1500 lm, 1000 lm or 700 lm		
Selectable colour temperature	3000K or 4000K		
Smart daylight sensor	Standby at dusk, full light when motion is detected and switches off automatically with morning light		
Integrated motion sensor	2 & 3-step dimming to standby level or off		
Warranty*	5 years (Battery 2 year)		

Data subject to change without notice * Refer to warranty policy