



NEWPORT SPIKE SL7261TC - 5W

IP54 MR16 LED lamp base spike luminaire with selectable CCT lamp

Application

Decorative accent solution

Design Specifications

- Machined 316L stainless steel or extruded aluminium body profile, black or silver or anodized silver finish
- Clear tempered glass cover
- GU5.3 lamp base, MR16 5W TC lamp included
- 600 mm 2 core rubber flex
- 12V AC or DC driver required
- SAL lamp options - MR16/7W, MR16DIM9W (excluding Stainless Steel fittings)

Performance

- Dimmable - **NO**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Input Voltage (V/DC)	Power (W)	Lumens (lm)	CCT (K)
	SL7261TC/SLS	12	12	5	360/400/380	3000/4000/6000
	SL7261TC/SL	12	12	5	360/400/380	3000/4000/6000
	SL7261TC/BK	12	12	5	360/400/380	3000/4000/6000
	SL7261TC/AS	12	12	5	360/400/380	3000/4000/6000

CRI	Beam Angle (°)	Mass (kg)	Diameter (mm)	Dim (mm)	Base Type	Body Colour
80	38	0.9	63	200(H) x 90(D)	GU5.3	STAINLESS STEEL
80	38	0.43	63	200(H) x 90(D)	GU5.3	SILVER
80	38	0.43	63	200(H) x 90(D)	GU5.3	BLACK
80	38	0.43	63	200(H) x 90(D)	GU5.3	ANODISED SILVER

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

SL7261

