



LT SERIES LT409TC - 9W


9 watt LED SMD tubular lamps, with selectable colour temperature

Application

Energy efficient LED lamp solutions

Design Specifications

- Opal polycarbonate diffuser
- Poly covered aluminium body
- High efficiency SMD LED chips, beam 200 degree
- Integral non-dimmable LED driver
- Selectable colour temperature 3000K / 4000K / 6000K, CRI > 80
- Suits most CFL lamp fitting, lamp bases B22, E27, double insulation



-
-
-
-
-
-
-
-
-
-
-
-
-

Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI	Beam Angle (°)
LT409TC/B22	240	9	850/900/850	3000/4000/6000	80	200
LT409TC/E27	240	9	850/900/850	3000/4000/6000	80	200



Technical Specification

Model No.	Dimmable	Diameter (mm)	Length (mm)	Base Type
LT409TC/B22	NO	40	101	B22
LT409TC/E27	NO	40	102	E27

IMPORTANT, where CCT selection switching is provided, it is important to switch OFF the SUPPLY before the CCT selection is made, otherwise equipment damage may occur.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions



LT407 B15



LT407 B22







LT407 E14



LT407 E27

Dimensions





Product Images



COOLUM PLUS.



TC SELECTABLE COLOUR

S9067TC 6 watt
dimmable downlight,
with selectable
colour temperature.

For more
information
please
scan me

