



PLUTO 1150 QP - 60W 700/1150mA

Australian approved 1-10V dimmable constant current LED driver with selectable output

Application

The perfect choice for constant current electronic lighting circuits

Design Specifications

- SELV and EMC compliant, safe no load operation
- Compact design profile
- Overload and short circuit protection
- Dimmable 1-10V, dimming range 10%~100%
- Secondary output range:
650/500/350/200mA (PLUTO 650/30QP/A),
1150/1000/850/700mA (PLUTO 1150/60QP/A)
- Auxiliary 12V DC power source (maximum sink current 40mA), Electrical class II, Do Not Cover.



Performance

- Dimmable - **YES**
- Dimmer Type - **1-10V**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Frequency (Hz)	Output Current (mA)	Power (W)	Power Factor
	PLUTO 1150/60QP/A	240	50	1150	60	0.9

Dimmable	Dim (mm)
YES	180(L) x 46(W) x 30(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".