



KEW SL9721 - 20/35W


IP65 LED weatherproof batten 20/35 watt selectable power and sensor options

Application

Multi-purpose ceiling mount or suspended, commercial or industrial applications

Design Specifications

- Vandal resistant design, robust polycarbonate body and UV stabilized polycarbonate diffuser
 - 301 Stainless steel clips & screws, IP65, IK08, sensor and emergency options
 - Operating temperature -20°C to +40°C
 - Integral constant current non-dimmable LED driver
 - Selectable power choices of 100%, 75% or 50%
 - Optional corridorSTANDBY functions available
- Product selections compliant to AS/NZS2293
- Emergency Lighting & Exit Signs are located in the **interior** and **exterior** emergency sections of this web catalogue



Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **Trailing edge, 1-10V, DALI, DSI**
- In Built Sensor - **OPTIONAL**
- Sensor Type - **MICROWAVE**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CRI	CCT (K)
	SL9721/20W WW	240	20	900/1800	80	3000
	SL9721/20W DL	240	20	900/1800	80	5000
	SL9721/20W/C	240	20	900/1800	80	5000
	SL9721/35W WW	240	35	1800/3600	80	3000
	SL9721/35W DL	240	35	1800/3600	80	5000
	SL9721/35W/C	240	35	1800/3600	80	5000
SL9721 CLIPS						

Beam Angle (°)	Body Colour	Dim (mm)	IPART	VEET
120	GREY	618(L) x 116(W) x 74(H)	YES	YES
120	GREY	618(L) x 116(W) x 74(H)	YES	YES
120	GREY	618(L) x 116(W) x 74(H)		
120	GREY	1215(L) x 116(W) x 74(H)	YES	YES
120	GREY	1215(L) x 116(W) x 74(H)	YES	YES
120	GREY	1215(L) x 116(W) x 74(H)		
PLASTIC CLIPS				

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

Sensor Options

- Integrated microwave motion sensor
- Integrated microwave motion sensor with corridorSTANDBY function

Emergency Options

- Product selections compliant to AS/NZS2293 Emergency Lighting & Exit Signs are located in the interior and exterior emergency sections of this catalogue.

Surface/suspended mounting clips to maintain IP rating



Surface mounting bracket Suspension bracket



Stainless steel clips can be fastened with extra locking screws for security

Accessories Included

- Allen key & screws
- PVC cable glands
- Suspension brackets

Installation type


- Surface mounted
- Suspended (Suspension kit is required)

Photometric Data

Photometric Data (at maintained power)

Unit: cd C0/C180 — C90/C270

SL9721/20W WW at 3000K



SL9721/35W DL at 5000K

