




SKYLUX

SKYLUX-200W

SAP CODE: 2001898



200W, 0-10V Dimming,
Wide voltage range,
110° Beam angle LED
Highbay


A versatile, cost effective LED
Highbay for lighting large
industrial spaces

Accessories

BRACKET; MICROWAVE SENSOR;
REMOTE



Photometric
Diagram



Unit: cd

- C0/180 114.0deg
- C90/270 114.0deg

KEY INFORMATION

Lumen Output	28850lm
Input Power	200W
Dimming Options	0-10V Dimming
Trim Colour	BLACK
Warranty	5yr
IP Rating	IP65
IK Rating	IK08
Rebate Scheme Approvals	VEET; REES; IPART

PHOTOMETRIC

Efficacy	157lm/W
LED	SMD
CCT	5000K
CRI	>70
Beam Angle	110°

ELECTRICAL

Driver	Integral
Supply Input	100-277V, 50/60Hz
Driver Output Voltage	120VDC
Power Factor	>0.9
LED Input Current (nominal)	1670mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Aluminium ADC12
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	1.5m Flex & Plug
Total Weight	5kg
Dimensions	Ø400 x 185mm
Operating Ambient Temp.	-35 to 50°C
Electrical Classification	Class 1