



# PROXIMA TRI

## Outdoor Floodlights

  
**TRITONE**  
Colour  
Changeable

  
**IP54**  
Ingress  
Protection  
Rating

  
**50,000hr**  
Expected  
Lifetime

  
**3yr**  
Warranty

### Sleek and robust.

PROXIMA-TRI is available in a single or twin lamp option for general security illumination. The sleek profile design with retrofittable PIR sensor makes it ideal for residential and commercial exterior applications.

### Features

- Tritone colour selectable
- Fully adjustable lamp position
- IP54 aluminium body
- PIR sensors for retrofitting
- Quick connect base
- Available in black or white finish

### Benefits

- Reduced SKUs and inventory levels
- Light exactly where its required
- Robust and durable
- Added security and safety when needed
- Ensures easy installation
- Blends in with architecture

## Product Overview

POWER	LAMPS	LUMENS	EFFICACY	CCT	DIMENSIONS	WEIGHT	COLOUR	SAP CODE	PRODUCT CODE
15W	Single	1000 lm	67 lm/W	3000K	Ø114 x 200mm	0.50kg	Black White	2001998 2002058	<b>PROXIMA-TRI15</b> <b>PROXIMA-TRI15-W</b>
		1100 lm	73 lm/W	4000K					
		1000 lm	67 lm/W	5000K					
30W	Dual	2000 lm	67 lm/W	3000K	Ø114 x 200mm	0.80kg	Black White	2002000 2002059	<b>PROXIMA-TRI30</b> <b>PROXIMA-TRI30-W</b>
		2200 lm	73 lm/W	4000K					
		2000 lm	67 lm/W	5000K					

### SPECIFICATIONS

<b>Body Material:</b>	Aluminium and Polycarbonate	<b>Driver:</b>	Integral
<b>Diffuser Material:</b>	PMMA (Acrylic)	<b>Power Connection:</b>	Terminal Block
<b>Body colour:</b>	Black White	<b>Input:</b>	220-240V, 50/60Hz
<b>IP Rating:</b>	IP54	<b>Electrical Classification:</b>	Class 1
<b>Beam Angle:</b>	100°	<b>Power Factor:</b>	>0.9
<b>Adjustable Angle:</b>	0-180°	<b>Protection:</b>	Overload / Short Circuit
<b>CRI:</b>	>80	<b>Lifespan:</b>	>50,000hrs @Ta25°C (L70)
<b>SDCM:</b>	<5	<b>Operating Ambient Temperature:</b>	-20 to 40°C
		<b>Dimming:</b>	Non-Dimmable

### APPLICATIONS

Residential  
Car Parks  
Garages  
Gardens  
External Walkways

### ACCESSORIES

**PIR Sensor (Black)**  
**PROXIMA-PIR-B**  
(SAP 2002061)



**PIR Sensor (White)**  
**PROXIMA-PIR-W**  
(SAP 2002060)



<b>Sensor Type:</b>	Passive Infrared
<b>Detection Distance:</b>	2 to 12m (Adjustable)
<b>Detection Range:</b>	180°
<b>Ambient Light:</b>	10 to 2000Lux (Adjustable)
<b>Time Delay:</b>	10 sec (± 3sec) to 7min (± 2min)
<b>Manual Override:</b>	Turn light off and on within 3s



PROXIMA-TRI15



PROXIMA-TRI15-W




PROXIMA-TRI30




PROXIMA-TRI30-W


### DIMENSIONS



PROXIMA-TRI15



PROXIMA-TRI30



FIND OUT MORE:

