UMBRA WIREGUARD to



ADVANCED



FEATURES

- Fully compliant (AS/NZS 2293)
- Emergency and non-emergency models available
- Works as Single Point Units (SPU) out of the box












UMBRA WIREGUARD ADVANCED



PRODUCT RANGE			
ORDER CODE	PRODUCT NUMBER	SKU	QTY
EV-UMBRA-ADV-WG-1200-EM Advanced 1200 mm Wireguard Emergency Batten	9336462121870	12187	4
EV-UMBRA-ADV-WG-1200 Advanced 1200 mm Wireguard Batten	9336462121856	12185	4

GENERAL FEATURES

- Tri-colour selection
- Emergency and non-emergency models

EMERGENCY MODELS (-EM)

- High Quality Lithium battery (LiFePO₄) and smart charger
- Fully compliant (AS/NZS 2293.3)

BUILT TO LAST

- Long life electronics
- LED Lifetime 50,000 hours (L70/B50)
- 7 Years Design Life 60,000 hours at max. ambient

SUITABLE INSTALLATION TYPES (OUT OF THE BOX)

Standalone (SPU)

ACCESSORY RANGE		
ORDER CODE	DESCRIPTION	SKU
EV-WIREGUARD-1200MM	Wireguard for 1200 mm Battens	
EV-1500MAH-6.4V-LIFEPO4	1500mAH 6.4V 2 Cell LiFePO, Battery	01302

OPERATIONA	L INFORMATION		
GENERAL			
Voltage	240V~ 50Hz		
Ambient temp.	0 to 40°C		
Class	1		
Wiring	Terminal block (1-16 mm □)		
Mounting type	Surface		
IP rating	IP20		
CRI	80	SDCM	< 4
EMERGENCY			
Rated duration	90 / 120 min		
Classification	C0:D50, C90:D25		
LAMP POWER			
Emergency	22 / 38 W		
Non-emergency	22 / 38 W		
COLOUR TEMP.	LUMENS (22W)	LUMENS (38W)	
4000K	> 2400	> 4100	
5000K	> 2400	> 4100	
6000K	> 2400	> 4100	
BATTERY		CHARGE	
Туре	LiFePO ₄	Туре	Smart charge
Voltage	6.4 V	Time	16 Hours
Code	01302	Operation	Multi-state
CONSTRUCTION			
Body	Powder coated steel	Diffuser	Acrylic
Gear tray	Powder coated steel	Endcaps	PC
COMPLIANCE			
Standards	AS/NZS 60598.2.22 AS/NZS 2293.3	IEC 60598-2-22 AS CISPR 15	

NOTE: For more information on the chemical resistance of our polycarbonate

or our compliance documentation, please see our website.

ektor.com.au **E: sales@evolt.com.au** P:1300 4EVOLT (438 658)

