

AT9480

5W ST64 LED Filament lamps. Dimmable, Clear Lens

Features

- Energy efficient LED lamp
- Long Life
- No mercury Content
- Suitable replacement for halogen and incandescent lamps
- Suitable for use with dimmers

Selected Models

- Stylish filament lamp with Glass body



MECHANICAL

Adjustability	Fixed
Diffuser Material	Glass
Product Finish	Clear
Fitting Colour	
AT9480/BC/WW/C AT9480/ES/WW/C	Clear
AT9480/BC/WW/GC AT9480/ES/WW/GC	Amber
AT9480/BC/WW/GC AT9480/ES/WW/GC	Golden
IC Rating	Non-IC
IP Rating	IP20

ELECTRICAL

Input Frequency (Hz)	50
Input voltage	230Vac
In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%	
Maximum Wattage (W)	5
Power Factor	0.7
Switch Type	Inline
System Max Wattage (W)	
AT9480/BC/WW/C AT9480/BC/WW/GC AT9480/ES/WW/C AT9480/ES/WW/GC	5
AT9480/BC/WW/GC AT9480/ES/WW/GC	5.1

Working Temp Range (C) -20 to 40

LAMP

Beam Angle (Deg)	
AT9480/BC/WW/C AT9480/BC/WW/GC AT9480/ES/WW/C AT9480/ES/WW/GC	270
AT9480/BC/WW/GC AT9480/ES/WW/GC	360
Bulb Type	ST64
CCT Configuration	Single
CRI	>80
Globe Base	
AT9480/BC/WW/C AT9480/BC/WW/GC	B22 / BC
AT9480/ES/WW/C AT9480/ES/WW/GC	E27
Globe Included	Yes
Led Package	2835
Number of Lamps	1



LED LIFETIME

LED Lifetime (hr)	15000
--------------------------	-------

This is the Reported LED Lifetime in Hours based on TM-21. Atom does not list the projected or calculated LED lifetime, which is normally longer as TM-21 Addendum B explicitly states " The Calculated and Projected Lp(Dk) are not to be reported: This Lifetime refers to the life of a single LED however the system life is longer since the probability and binomial distribution of all LEDs in the system means that the average led is performing above the specification and compensates for the LEDs falling below.

COLOUR TEMPERATURE

CCT (K)

AT9480/BC/WW/C AT9480/BC/WW/GC AT9480/ES/WW/C AT9480/ES/WW/GC	2700
--	------

AT9480/BC/WW/GC AT9480/ES/WW/GC	2500
--	------

CCT Colour	Warm White
-------------------	------------

System Lumens (L)

AT9480/BC/WW/C AT9480/ES/WW/C	470
--	-----

AT9480/BC/WW/GC AT9480/ES/WW/GC	430
--	-----

AT9480/BC/WW/GC AT9480/ES/WW/GC	360
--	-----

DRIVER

Dimmable	Yes
-----------------	-----

Driver Included	Yes
------------------------	-----

Integrated Driver	Yes
--------------------------	-----

Driver Type	Dimmable (Phase cut)
--------------------	-----------------------

COMPLIANCE

Standards	AS/NZS 62560 IEC/TR 62778 AS CISPR 15
------------------	---

WARRANTY

Commercial Use Warranty	1 RTB (Total 1 Year)
--------------------------------	----------------------

Maximum Use Daily (hr)	10
-------------------------------	----

Domestic Use Warranty	1 (Yr) RTB
------------------------------	------------

Operational Lifetime (hr)	15000
----------------------------------	-------

VIP Warranty (Yr)	2 RTB (Total 2 Years)
--------------------------	-----------------------

DIMENSIONS

Product Height (mm)

AT9480/BC/WW/C AT9480/BC/WW/GC AT9480/ES/WW/C AT9480/ES/WW/GC	130
--	-----

AT9480/BC/WW/GC AT9480/ES/WW/GC	150
--	-----

Product Width (mm)	64
---------------------------	----



AT9480/ES/WW/GC

Ordering Information

Order code	Item Code	Description
18950	AT9480/BC/WW/C	5W ST64 LED FILAMENT LAMP B22 WW DIMMABLE CLEAR
18951	AT9480/BC/WW/GC	5W ST64 LED FILAMENT LAMP B22 WW DIMMABLE AMBER
10880	AT9480/BC/WW/GC	ST64 Filament 5.1W Dimmable 2500K BC/B22 Golden Clear
18948	AT9480/ES/WW/C	5W ST64 LED FILAMENT LAMP E27 WW DIMMABLE CLEAR
18949	AT9480/ES/WW/GC	5W ST64 LED FILAMENT LAMP E27 WW DIMMABLE AMBER
10840	AT9480/ES/WW/GC	ST64 Filament 5.1W Dimmable 2500K ES/E27 Golden Clear

Photometrics

[AT9480/BC/WW/C](#)

[AT9480/BC/WW/GC](#)

[AT9480/ES/WW/C](#)