

AT9482

2W ST26 LED Globes Non Dimmable, Clear lens

Features

- Energy efficient LED lamp
- Long Life
- No mercury Content
- Suitable replacement for halogen and incandescent lamps
- Stylish filament lamp with Glass body



MECHANICAL

Adjustability	Fixed
Diffuser Material	Glass
Product Finish	Clear
Fitting Colour	Clear
IC Rating	Non-IC
IP Rating	IP20

ELECTRICAL

Input Frequency	50 Hz
Input voltage	230Vac

In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%

Maximum Wattage	2 W
Switch Type	Inline
System Max Wattage	2 W
Working Temp Range	-20 to 40 °C

LAMP

Beam Angle	360 °
Bulb Type	ST26
CCT Configuration	Single
CRI	>80
Globe Base	
AT9482/SBC/WW	B15 / SBC

AT9482/SES/WW

E14 / SES

Globe Included	Yes
Led Package	2835
Number of Lamps	1

LED LIFETIME

LED Lifetime	15000 hrs
---------------------	-----------

This is the Reported LED Lifetime in Hours based on TM-21. Atom does not list the projected or calculated LED lifetime, which is normally longer as TM-21 Addendum B explicitly states "The Calculated and Projected Lp(Dk) are not to be reported". This Lifetime refers to the life of a single LED however the system life is longer since the probability and binomial distribution of all LEDs in the system means that the average led is performing above the specification and compensates for the LEDs falling below.

COLOUR TEMPERATURE

CCT	3000 K
CCT Colour	Warm White
System Lumens	230 lm

All photometric data has a tolerance of ±10%.

DRIVER

Dimmable	No
Driver Included	Yes
Integrated Driver	Yes
Driver Type	Fixed output

COMPLIANCE

Product Design Life 10 years

The product design life relates to the total product life which includes LEDs, drivers and the enclosure. This is different to the LED lifetime which only refers to the economical lifetime of the LEDs at which time the lumen output has dropped below the L Value. The product design life is calculated at the maximum ambient or working temperature of the product and takes into account the Daily Use.

Daily Use 4 hrs

The Daily Use is the recommended time required to meet the product's design life. Installations can exceed this time, however the product design life will be reduced proportionally.

Standards AS/NZS 62560
IEC/TR 62778
AS CISPR 15

WARRANTY

Domestic Use Warranty 1 (Yr) RTB

VIP Warranty 2 RTB (Total 2 Years)

VIP warranty is available to registered users and is subjected to additional terms and conditions.

Warranty Operating Hours 500 hrs

This product is provided with a warranty up until the stated warranty period or until the stated warranty operating hours has been reached (whichever occurs first).

DIMENSIONS

Product Height 60 mm

Product Width 26 mm

Ordering Information

Order code	Item Code	Description
18733	AT9482/SBC/WW	2W ST26 LED FILAMENT PILOT LAMP B15 WW NON-DIM CLEAR
18732	AT9482/SES/WW	2W ST26 LED FILAMENT PILOT LAMP E14 WW NON-DIM CLEAR

Photometrics

AT9482/SBC/WW

