





COOLUM PLUS S9167TC - 6W

6 watt dimmable, LED TILT downlight, with selectable CCT

Application

Ideal for residential or commercial interior applications

Design Specifications

- 6 watt integral flickerCONTROLLED dimmable driver, complete with flex & plug for easy installation
- High efficiency LED optics, multi-faceted optical system
- Selectable CCT 3000K / 4000K / 5700K, CRI > 90, 40° beam distribution, 30° tilt
- Polyamide trim and body in white or black
- IC 4 rated, double insulated

Performance

- Dimmable YES
- Dimmer Type TRAILING EDGE























Technical Specification

| Product | Model No. | Input Voltage (V/AC) | Power (W) | Lumens (lm) | сст (к) | Beam Angle (°) |
|---------|------------|-------------------------|--------------|----------------|----------------|-------------------|
| | S9167TC/WH | 240 | 6 | 500/560/540 | 3000/4000/5700 | 40 |
| | S9167TC/BK | 240 | 6 | 500/560/540 | 3000/4000/5700 | 40 |


| Dimmable | CRI | Body Colour | Cut Out (mm) | Diameter (mm) | Dim (mm) |
|----------|-----|-------------|--------------|---------------|----------|
| YES | 90 | WHITE | 72 | 90 | 61(H) |
| YES | 90 | BLACK | 72 | 90 | 61(H) |

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





Dimensions



Photometric Data





