



COOLUM PLUS S9069/TC - 12W

12 watt dimmable LED downlight, UGR<19, with selectable CCT

Application

Perfect for residential or commercial applications

Design Specifications

- 12 watt integral flickerCONTROLLED dimmable driver complete with flex & plug for easy installation
- High efficiency LED optics, multi-faceted optical system
- Selectable CCT 3000K / 4000K / 5700K, CRI>90, 60° beam distribution, UGR<19
- Polyamide trim and body form white or black
- IC - 4 rated, double insulated

Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge**



Technical Specification


Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9069TC/WH	240	12	840/920/900	3000/4000/5700	60
	S9069TC/BK	240	12	680/740/720	3000/4000/5700	60

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	90	WHITE	120	140	140(W) x 102(H)
YES	90	BLACK	120	140	140(W) x 102(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

Dimensions



Photometric Data

Photometric Data

Unit: cd C0/C180 C90/C270

