Catalogue No: **CEP7-1EEGE** OVERLOAD ELECTRONIC CEP7-1 BASIC 20-100A FOR CA7-60/97

Motor Control and Drives > Motor Starting and Protection > Motor Protection > Sprecher + Schuh Overloads > CEP7 Gen 3 Electronic Overloads





OVERLOAD ELECTRONIC CEP7-1 BASIC 20-100A FOR CA7-60/97

- CEP7-1EE: Trip Class 10 and 20, manual reset only
- CEP7-1EF: Trip Class 10, 15, 20, 30, manual or automatic reset
- 5:1 wide current adjustment range to cover a variety of motor applications
- Supports both single and three-phase operation in a single component
- A variety of accessories available for enhanced protection
- Current measurement-based protection
- Electronic design and therman memory
- Phase loss protection
- Self-powered and direct-mount design with CA7 contactors

Representative Photo Only

(actual product may vary based on configuration selections)

SPECIFICATIONS	
Product Series	CEP7-1
Component Type Motor Control and Drives	Electronic Overload
Adjustment	5 : 1
Current Range (A)	20 - 100
Approx kW	11-55
kW Rating, AC-3, 415V, Min	11 kW @415V min
kW Rating, AC-3, 415V, Max	55 kW @415V max
Motor FLC, Min	20 A, min
Motor FLC, Max	100 A, max
REFERENCES	
IECEx Certificate -	
Supplier Declaration of Conformity:	
Installation Guide: -	
User Manual: -	
Manufacturer Datasheet: -	

Manufacturer Catalogue & Product Selection:

