Catalogue No: CEP7-1EEDB

OVERLOAD ELECTRONIC CEP7-1 BASIC 3.2-16A FOR CA7-9/23

Motor Control and Drives > Motor Starting and Protection > Motor Protection > Sprecher + Schuh Overloads > CEP7





Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS

OVERLOAD ELECTRONIC CEP7-1 BASIC 3.2-16A FOR CA7-9/23

- CEP7-1EE: Trip Class 10 and 20, manual reset only
- CEP7-1EF: Trip Class 10, 15, 20, 30, manual or automatic reset
- 5:1 wide current adjustment range to cover a variety of motor applications
- Supports both single and three-phase operation in a single component
- A variety of accessories available for enhanced protection
- Current measurement-based protection
- Electronic design and therman memory
- Phase loss protection
- Self-powered and direct-mount design with CA7 contactors

| of Edit Ida Hollo | |
|---|---------------------|
| Product Series | Sprecher + Schuh |
| Component Type Motor Control and Drives | Electronic Overload |
| Adjustment | 5:1 |
| Current Range (A) | 3.2 - 16 |
| Approx kW | 1.5-7.5 |
| kW Rating, AC-3, 415V, Min | 1.5 kW @415V min |
| kW Rating, AC-3, 415V, Max | 7.5 kW @415V max |
| Motor FLC, Min | 1.5 A, min |
| Motor FLC, Max | 7.5 A, max |
| Trip Class | Adjustable 10, 20 |
| Reset | Manual Only |
| Manual Reset | Yes Y/N |
| Rated Operation Voltage | 690 V AC |
| REFERENCES | |
| IECEx Certificate - | |
| Supplier Declaration of Conformity: | |
| Installation Guide: - | |
| User Manual: - | |
| Manufacturer Datasheet: - | |
| Manufacturer Catalogue & Product Selection: | |
| | |

