Catalogue No: CEP7-1EFDB

OVERLOAD ELECTRONIC CEP7-1 ADVANCED 3.2-16A FOR CA7-9/23

Motor Control and Drives > Motor Starting and Protection > Motor Protection > Sprecher + Schuh Overloads > CEP7





Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS

OVERLOAD ELECTRONIC CEP7-1 ADVANCED 3.2-16A FOR CA7-9/23

- CEP7-1EE: Trip Class 10 and 20, manual reset only
- CEP7-1EF: Trip Class 10, 15, 20, 30, manual or automatic reset
- 5:1 wide current adjustment range to cover a variety of motor applications
- Supports both single and three-phase operation in a single component
- A variety of accessories available for enhanced protection
- Current measurement-based protection
- Electronic design and therman memory
- Phase loss protection
- Self-powered and direct-mount design with CA7 contactors

Product Series		Sprecher + Schuh
Component Type Motor Control and Drives		Electronic Overload
Adjustment		5:1
Current Range (A)		3.2 - 16
Approx kW		1.5-7.5
kW Rating, AC-3, 415V, Min		1.5 kW @415V min
kW Rating, AC-3, 415V, Max		7.5 kW @415V max
Motor FLC, Min		3.2 A, min
Motor FLC, Max		16 A, max
Trip Class		Adjustable (10, 15, 20, 30)
Reset		Automatic / Manual
Automatic Reset		Yes Y/N
Manual Reset		Yes Y/N
Rated Operation Voltage		690 V AC
REFERENCES		
IECEx Certificate	-	
Supplier Declaration of Conformity:	-	
Installation Guide:	-	
User Manual:	-	
Manufacturer Datasheet:	-	
Manufacturer Catalogue & Product Selection:	-	

