

AT9479 UV

AT9479/ES/UV

12W A60 UV LED Lamps. Non Dimmable

Features

- UV Blacklight, Ideal for illuminating most reactive pigments, paints and dyes with black light
- Energy efficient LED lamp
- Long Life
- No mercury Content
- Suitable replacement for halogen and incandescent lamps



ORDERING INFORMATION

Order code	18952
Description	12W A60 UV BLACKLIGHT LED LAMP E27 NON-DIMM
Driver Type	Fixed output
Item Code	AT9479/ES/UV

MECHANICAL

Adjustability	Fixed
Diffuser Material	Polycarbonate
Product Finish	Frosted
Fitting Colour	White
IP Rating	IP20

ELECTRICAL

Input Frequency	50 Hz
Input voltage	230Vac
In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%	
Maximum Wattage	12 W
Power Factor	0.55
Switch Type	Inline
System Max Wattage	12 W
Working Temp Range	-20 to 40 °C

LAMP

Bulb Type	A60
CCT Configuration	Single
CRI	>80
Globe Base	E27
Globe Included	Yes
Led Package	2835
Number of Lamps	1

LED LIFETIME

LED Lifetime	15000 hrs
This is the Reported LED Lifetime in Hours based on TM-21. Atom does not list the projected or calculated LED lifetime, which is normally longer as TM-21 Addendum B explicitly states "The Calculated and Projected Lp(Dk) are not to be reported". This Lifetime refers to the life of a single LED however the system life is longer since the probability and binomial distribution of all LEDs in the system means that the average led is performing above the specification and compensates for the LEDs falling below.	

COLOUR TEMPERATURE

CCT	25000 K
CCT Colour	UV



DRIVER

Dimmable	No
Driver Included	Yes
Integrated Driver	Yes
Driver Type	Fixed output

COMPLIANCE

Product Design Life	10 years
----------------------------	----------

The product design life relates to the total product life which includes LEDs, drivers and the enclosure. This is different to the LED lifetime which only refers to the economical lifetime of the LEDs at which time the lumen output has dropped below the L Value. The product design life is calculated at the maximum ambient or working temperature of the product and takes into account the Daily Use.

Daily Use	4 hrs
------------------	-------

The Daily Use is the recommended time required to meet the product's design life. Installations can exceed this time, however the product design life will be reduced proportionally.

Standards	AS/NZS 62560 IEC/TR 62778 AS CISPR 15
------------------	---

WARRANTY

Domestic Use Warranty	1 (Yr) RTB
------------------------------	------------

VIP Warranty	2 RTB (Total 2 Years)
---------------------	-----------------------

VIP warranty is available to registered users and is subjected to additional terms and conditions.

Warranty Operating Hours	500 hrs
---------------------------------	---------

This product is provided with a warranty up until the stated warranty period or until the stated warranty operating hours has been reached (whichever occurs first).

DIMENSIONS

Product Height	120 mm
-----------------------	--------

Product Width	60 mm
----------------------	-------