Catalogue No: DTCB10HSHT220415

SHUNT TRIP 220 TO 415V AC SUITS DTCB10H

Power Distribution and Protection > Circuit Breakers > Miniature Circuit Breakers and Earth Leakage Protection (RCDs and RCBOs) > DIN-T Accessories > DIN-T Shunt Trip > Shunt Trip



DTCB10H Shunt Trip 220-415V AC

- Shunt trip are supplied as a kit for field fitting to MCBs
- Wide range of voltages in both AC and DC

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Product Series	DIN-T
Component Type Power Distribution & Protect	tion Shunt Trip
Wire / Conductor Size, Flex Cable, Min	1 mm² min
Wire / Conductor Size, Flex Cable, Max	2.5 mm ² max
Wire / Conductor Size, Rigid Cable, Min	1 mm ² min
Wire / Conductor Size, Rigid Cable, Max	35 mm² max
Storage Temperature, Min	-40 °C min
Storage Temperature, Max	70 °C max
Vibration Rating	IEC60068-2-30 IEC61373 Cat1 Class B
Standards Compliance	AS/NZS 60947-2; IEC 60947-2 UL 489
REFERENCES	
IECEx Certificate -	
Supplier Declaration of	
Installation Guide: -	
User Manual: -	
Manufacturer Datasheet: -	
Manufacturer Catalogue & Product Selection:	



Catalogue No: DTCB10HSHT220415

SHUNT TRIP 220 TO 415V AC SUITS DTCB10H

Power Distribution and Protection > Circuit Breakers > Miniature Circuit Breakers and Earth Leakage Protection (RCDs and RCBOs) > DIN-T Accessories > DIN-T Shunt Trip > Shunt Trip





