

Catalogue No: **CPLACC-3ME-O**

C/PLUS PBOARD ACC MOD WITH ESC 3M-648mm ORG

Power Distribution and Protection > Distribution Boards > Panelboards > CONCEPT PLUS Panelboard > CPL
Accessory Modules > Accessory Modules, Orange, Mild Steel



Representative Photo Only
(actual product may vary based on configuration selections)

CONCEPT PLUS Accessory Module, IP42, with Blank Escutcheon, 3M-648 mm, Orange (X15)

- Standard AS/NZS 61439-3
- Option - Compact 160 A or 250 A main switch
- Option - Isolator or circuit breaker main switch
- Modular sizes up to 96-Way
- Knockouts for up to 18 modules DIN equipment
- Accessory modules
- Removable gland plates
- Door fitted independent of escutcheon
- Right hand door hinging
- Semi flush door swing handle
- IP42 (option IP52)
- Chassis tee-off isolator option

SPECIFICATIONS

Product Series	Concept Plus
Component Type Power Distribution & Protection	Accessory Module
IP Rating	IP42
IP rating, with door	IP42
Width	600 mm
IP rating, without door	IP30
Box Size	3
Number of Modules	3 qty
Height	648 mm
Depth, Including Door	200 mm, incl door
Depth, Door	20 mm depth
Segregation Form Rating	1
Material	Powder Coated Mild Steel
Material Thickness	1.6 mm
Material, Base	Mild Steel
Material Thickness, Base	1.6 mm
Finish, Base	Powder Coated (Polyester) base
Colour, Base	Orange (X15) base
Material, door	Mild Steel
Material thickness, door	1.6 mm
Finish, Door	Powder Coated (Polyester) door
Colour, Door	Orange (X15) door
Door Handle Type	Semi flush keyed CL001 quarter turn
Escutcheon	Bright white gloss dished hinged RH side
Material, Escutcheon	Mild Steel
Material Thickness, Escutcheon	1 mm
Finish, Escutcheon	Powder Coated (Polyester) escutcheon
Colour, Escutcheon	White escutcheon

Catalogue No: **CPLACC-3ME-O**
C/PLUS PBOARD ACC MOD WITH ESC 3M-648mm ORG

Power Distribution and Protection > Distribution Boards > Panelboards > CONCEPT PLUS Panelboard > CPL
Accessory Modules > Accessory Modules, Orange, Mild Steel



Door hinged independent escutcheon	Yes, from RH side standard
Gland Plate/End Cap	Removable 1.6 mm mild steel, top/bottom
Ue, rated operational voltage, AC, 1ph, nom	240 V AC
Ue, rated operational voltage, AC, 3ph, nom	415 V AC
L99 Application	Concept Plus, 3 Module, Orange, Accessory Panelboard, with escutcheon
Style of Panelboard	Accessory Module
Standards Compliance	AS/NZS 61439.3

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	Concept Gen 3 Installation Instruction Booklet
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-