

Catalogue No: CPRACC-48-O

C/PREM PBOARD ACC MOD DIN 48WAY 2M-432mm ORG

Power Distribution and Protection > Distribution Boards > Panelboards > CONCEPT PREMIER Panelboard > Concept Premier Accessory Modules- CPRACC > Accessory Module Orange



CONCEPT PREMIER Accessory Module, IP66, DIN 48-Way with Cut-out Escutcheon, 2M-432 mm, Orange (X15)



- Standard AS/NZS 61439
- Compact 160 A or 250 A main switch option
- 400A Isolator main switch option
- Isolator or circuit breaker main switch option
- IP66
- Modular sizes up to 96-Way
- 1.6 mm fully welded construction
- Stainless Steel option
- Accessory modules
- Removable gland plates
- Door fitted independent of escutcheon
- Removeable hinged escutcheon
- Right hand door hinging as standard
- Semi flush swing handle, lockable door
- 3 point locking
- Chassis tee-off isolator option

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	Concept Premier
Component Type Power Distribution & Protection	Accessory Module
IP Rating	IP66
IP rating, with door	IP66
Width	600 mm
IP rating, without door	IP30
Number of Poles	48
	3
Number of Modules	2 qty
	432 mm
Depth, Including Door	mm, incl door
Depth, Door	20 mm depth
	1
Material	Powder Coated Mild Steel
Material Thickness	1.6 mm
Material, Base	Mild Steel
Material Thickness, Base	1.6 mm
Finish, Base	Powder Coated (Polyester) base
Colour, Base	Orange (X15) base
Material, door	Mild Steel
Material thickness, door	1.6 mm
Finish, Door	Powder Coated (Polyester) door
Colour, Door	door
Door Handle Type	Semi flush keyed CL001 quarter turn
Escutcheon	Bright white gloss dished hinged RH side
Material, Escutcheon	Mild Steel
Material Thickness, Escutcheon	1 mm
Finish, Escutcheon	Powder Coated (Polyester) escutcheon

Catalogue No: **CPRACC-48-O**

C/PREM PBOARD ACC MOD DIN 48WAY 2M-432mm ORG

Power Distribution and Protection > Distribution Boards > Panelboards > CONCEPT PREMIER Panelboard > Concept Premier Accessory Modules- CPRACC > Accessory Module Orange



Colour, Escutcheon	White escutcheon
Door hinged independent escutcheon	Yes, from RH side standard
Gland Plate/End Cap	Removable 2.0 mm mild steel, top/bottom
Spare DIN rail space (free poles)	48
Ue, rated operational voltage, AC, 1ph, nom	240 V AC
Ue, rated operational voltage, AC, 3ph, nom	415 V AC
L99 Application	Concept Premier, 2 Module, Orange, Accessory Panelboard, with double row 48W DIN rails and escutcheon
Style of Panelboard	Accessory Module

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	Concept Gen 3 Installation Instruction Booklet
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-