

RESPIRATORY GEAR

PROCHOICE P2 DISPOSABLE RESPIRATOR

PRODUCT DATA SHEET: PC305



PRODUCT CODE:
PC305



FEATURES AND BENEFITS

- P2 - Certified to AS/NZS 1716:2012 Respiratory protective devices.
- P2 Disposable respirator for protection against
- Mechanically and thermally generated particles.
- Lightweight cupped design for comfortable extended wear.
- Easily worn with glasses & goggles.
- Dual Quicklock head strap for ease of donning and doffing.
- Resealable bag for hygienic storage.

AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
PC305	SINGLE	20	20

PRODUCT DETAILS

Straps: Latex-free rubber band
Filter Media: Polypropylene melt-blown
Weight: 12.2g + 1g each

CARE INSTRUCTIONS

Shelf life of the unopened product is three (3) years from date of manufacture when stored within temperature range of -20oC to + 25oC and less than 80% relative humidity.

End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided.

Ensure disposable mask is correctly fitted prior to each use and conduct annual fit testing in accordance with AS/NZS 1715:2009.



HYGIENIC



PARTICULATE PROTECTION



RETAINS SHAPE



VALUE

WARNINGS AND USE LIMITATIONS

1. Facial hair has the potential to compromise the required protective seal of the respirator.
2. Ensure adequate oxygen levels are present.
3. Ensure the contamination is known and the respirator issuitable for the application.
4. Replace when taste, smell or the breathing resistance is high.
5. Store in a clean resealable storage device.

STANDARDS

AS/NZS 1716:2012 P2 rating.

Certified by Benchmark - Identification number: BMP547903.

To be used in conjunction with: AS/NZS 1715:2009

Selection, use and maintenance of respiratory protective equipment.



AS/NZS 1716:2012
ID No: **BMP547903**

CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only

APPLICATIONS

The Pro Choice Safety Gear range of respiratory gear is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, manufacturing, metal processing, mining and quarrying, transportation.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA
 12 FELLOWSHIP ROAD,
 GNANGARA, WA 6077
 TECH SUPPORT: 1300 275 820
 CUSTOMER SERVICE: 1300 770 723
 EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND
 7 SIR WOOLF FISHER DRIVE, Highbrook,
 EAST TAMAKI, AUCKLAND 2013
 TECH SUPPORT: 0800 888 778
 CUSTOMER SERVICE: 0800 888 778
 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
 PARAMOUNTSAFETY.COM

PRO
 PRO CHOICE SAFETY GEAR
 FROM
PARAMOUNT
 SAFETY PRODUCTS