

ZS250M3250TF

Terasaki TemBreak PRO ELCB 250 Frame 65kA 30mA 3A 3P
250A Adj. Thermal Fix. Magnetic



TERASAKI
Innovators in Protection Technology



Component type	Power switching circuit breaker
Range	TemBreak PRO
Model	N/A
Product status	Existing

The latest innovation of MCCBs from Terasaki, offering superior performance and versatility.

Rated current In	250.0 A
Number of poles	3.0
Max. rated operation voltage Ue AC	525.0 V
Rated ultimate short-circuit breaking capacity Icu at 415 V, 50 Hz	65.0 kA
Rated service short-circuit breaking capacity Ics at 415 V, 50 Hz	36.0 kA
Type of protection trip unit	Earth leakage circuit breaker
Trip curve	Adj. thermal, fixed magnetic
Frame size rating	250.0 A
Long time overload protection adjustment range	160 - 250 A
Position of connection for main current circuit	Front side
Integrated earth fault protection	Yes
Rated frequency	50 - 60 Hz
Rated insulation voltage Ui	525.0 V
Suitable for isolation	Yes
Rated impulse withstand voltage Uimp	8.0 kV
Over voltage category	IV
Reverse connection of supply possible	Yes
AC power loss per pole at In	18.33 W
Electrical life at Un, In (service cycles)	10000.0 cycles
Type of electrical connection of main circuit	Bolt connection
Power loss at rated current	55.0 W

Connectable conductor cross section	35 - 185 mm ²
DIN rail (top hat rail) mounting optional	Yes
Mechanical life (service cycles)	30000.0 cycles

ELECTRICAL

MECHANICAL

ZS250M3250TF

Terasaki TemBreak PRO ELCB 250 Frame 65kA 30mA 3A 3P
250A Adj. Thermal Fix. Magnetic



TERASAKI
Innovators in Protection Technology


MECHANICAL	Vibration acceleration (Max)	19.0 m/s ²
	Vibration frequency, operational (Max)	16.7 Hz
	Vibration duration (Max)	12.0 min
DIMENSIONS	Height	165.0 mm
	Width	90.0 mm
	Pole connection pitch	35.0 mm
	Built-in depth	68.0 mm
	Depth (toggle included)	92.0 mm
	Weight	1.5 kg
ENVIRONMENT	Pollution degree	3.0
	Rated surrounding temperature without derating	50.0 °C
	Ambient temperature during operating	-5 - 70 °C
	Max. temperature	70.0 °C
	Storage temperature	-10 - 70 °C
	Allowable relative humidity	0 - 85 %
CERTIFICATES/APPROVALS	Altitude before derating (Max)	2000.0 m
	Standard	AS/NZS IEC 60947.2

ZS250M3250TF

Terasaki TemBreak PRO ELCB 250 Frame 65kA 30mA 3A 3P
250A Adj. Thermal Fix. Magnetic



DIMENSIONAL DIAGRAM



ZS250M3250TF

Terasaki TemBreak PRO ELCB 250 Frame 65kA 30mA 3A 3P
250A Adj. Thermal Fix. Magnetic



RELATED PRODUCTS

ACCESSORY



Item No: T25CAPLAB

Required: No


Description: Terasaki TemBreak 2 Label for 250AF



Item No: T2AL00B1STA

Required: No

Description: Terasaki TemBreak PRO Alarm Switch for B Model 1 NO Contact Heavy Duty Type



Item No: T2AL00B2STA

Required: No

Description: Terasaki TemBreak PRO Alarm Switch for B Model 1 NC Contact Heavy Duty Type



Item No: T2AL00M3RTA

Required: No

Description: Terasaki TemBreak PRO Alarm Switch for B Model 1 CO Contact Microcurrent Type



Item No: T2AL00M3STA

Required: No

Description: Terasaki TemBreak PRO Alarm Switch for B Model 1 CO Contact General Type



Item No: T2AL00M3SWA

Required: No

Description: Terasaki TemBreak PRO Alarm Switch for B Model 1 CO Contact Wired Type



Item No: T2AX00B1STA

Required: No

Description: Terasaki TemBreak PRO Auxiliary Switch for B Model 1 NO Contact Heavy Duty Type



Item No: T2AX00B2STA

Required: No

Description: Terasaki TemBreak PRO Auxiliary Switch for B Model 1 NC Contact Heavy Duty Type



Item No: T2AX00M3RTA

Required: No

Description: Terasaki TemBreak PRO Auxiliary Switch for B Model 1 CO Contact Microcurrent Type



Item No: T2AX00M3STA

Required: No

Description: Terasaki TemBreak PRO Auxiliary Switch for B Model 1 CO Contact General Type



Item No: T2AX00M3SWA

Required: No


Description: Terasaki TemBreak PRO Auxiliary Switch for B Model 1 CO Contact Wired Type



Item No: T2BA25L3SH

Required: No


Description: Terasaki TemBreak PRO Interpole Barriers for A250/P250/ZS250 Qty 2



Item No: T2CF00L

Required: No

Description: Terasaki TemBreak PRO Terminal Cover Clip for ZS125/B160/ZS250/B250



Item No: T2CF253SLHP

Required: No


Description: Terasaki TemBreak PRO Terminal Cover CF Long Style for 3P ZS250 MCCB Qty 1



Item No: T2CF253SSHP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Short Style for 3P ZS250 MCCB Qty 1



Item No: T2CF253SSNP

Required: No


Description: Terasaki TemBreak PRO Terminal Cover CF Short Style for 3P ZS250 MCCB Qty 2



Item No: T2CF253WC

Required: No

Description: Terasaki TemBreak 2 Terminal Screen Front Connect for E250/S250 3P MCCBs



Item No: T2CR254SHP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CR Flush Style for B250/ZS250 4P MCCB Qty 1


ZS250M3250TF

Terasaki TemBreak PRO ELCB 250 Frame 65kA 30mA 3A 3P
250A Adj. Thermal Fix. Magnetic



RELATED PRODUCTS

ACCESSORY



Item No: T2CR254SNP

Required: No


Description: Terasaki TemBreak PRO Terminal Cover CR Flush Style for B250/ZS250 4P MCCB Qty 2



Item No: T2CS161SP

Required: No


Description: Terasaki TemBreak PRO Terminal Cover CS Standard Style for B160 1P MCCB Qty 2



Item No: T2CS253SHP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CS Standard Style for ZS250 3P MCCB Qty 1



Item No: T2CS253SNP

Required: No


Description: Terasaki TemBreak PRO Terminal Cover CS Standard Style for ZS250 3P MCCB Qty 2



Item No: T2FB251BA

Required: No

Description: Terasaki TemBreak 2 Attached Busbars for 160 to 250 1P MCCBs Qty 2



Item No: T2FB25L3SH

Required: No


Description: Terasaki TemBreak PRO Straight Extension Bars 3P A/P/B/ZS250 MCCB Qty 3



Item No: T2FB25L3WH

Required: No

Description: Terasaki TemBreak PRO Flanged Extension Bars 3P A/P/B/ZS250 MCCB Qty 3



Item No: T2FW25L3B

Required: No

Description: Terasaki TemBreak PRO Tunnel Terminal fits 35 to 120nm2 for B250/ZS250 Qty 6



Item No: T2HB25UR5BNP

Required: No

Description: Terasaki TemBreak PRO Handle Direct Mount with Door Interlock for B250/ZS250 Black



Item No: T2HB25UR5RNP

Required: No

Description: Terasaki TemBreak PRO Handle Direct Mount with Door Interlock for B250/ZS250 Red



Item No: T2HL25B

Required: No

Description: Terasaki TemBreak PRO Non Captive Toggle Lock 5 x 16.5mm Slot for ZS125/ZS250/B125/B160/B250



Item No: T2HL25CAP

Required: No

Description: Terasaki TemBreak 2 Toggle Lock Captive for 250 MCCBs



Item No: T2HP25PALK

Required: No

Description: Terasaki TemBreak 2 Handle Mechanism Padlock Device for 125A/250A MCCBs



Item No: T2HP25R6BN

Required: No

Description: Terasaki TemBreak 2 Handle Extension IP65 for 160 to 250 MCCBs Black



Item No: T2HP25R6ME

Required: No

Description: Terasaki TemBreak 2 Handle Metal IP65 for 160 to 250



Item No: T2HP25R6RN

Required: No

Description: Terasaki TemBreak 2 Handle Extension IP65 for 160 to 250 MCCBs Red



Item No: T2HS250SHAFT

Required: No

Description: Terasaki TemBreak 2 Handle Shaft 90mm for 125/250 MCCBs



Item No: T2HSESC100

Required: No

Description: Terasaki TemBreak 2 Handle Label Plate 100mm MCCBs

ZS250M3250TF

Terasaki TemBreak PRO ELCB 250 Frame 65kA 30mA 3A 3P
250A Adj. Thermal Fix. Magnetic



RELATED PRODUCTS

ACCESSORY



Item No: T2M1166CBA

Required: No

Description: Terasaki TemBreak 2 ZS Trip Test Earth Leakage Module 3P plus Neutral



Item No: T2MC25A10NB

Required: No

Description: Terasaki TemBreak 2 Motor 110V AC for 160/250 MCCBs



Item No: T2MC25A24NB

Required: No

Description: Terasaki TemBreak 2 Motor 240V AC for 160/250 MCCBs



Item No: T2MC25D02NB

Required: No

Description: Terasaki TemBreak 2 Motor 24V DC for 160/250 MCCBs



Item No: T2MC25D10NB

Required: No

Description: Terasaki TemBreak 2 Motor 110V DC for 160/250 MCCBs



Item No: T2MM25L05A

Required: No

Description: Terasaki TemBreak PRO Motor Interlock Cable 0.5m for A/P/B/ZS MCCB Rated 12-250A



Item No: T2MM25L15A

Required: No

Description: Terasaki TemBreak PRO Motor Interlock Cable 1.5m for A/P/B/ZS MCCB Rated 12-250A



Item No: T2MM40S06A

Required: No

Description: Terasaki TemBreak PRO Motor Interlock Cable 0.6m for B250/ZS250 with 630 to 1000A MCCB



Item No: T2MM40S21A

Required: No


Description: Terasaki TemBreak PRO Motor Interlock Cable 2.1m for P160/P250 with 400 to 1000A MCCB



Item No: TPHS25SR5GM

Required: No

Description: Terasaki TemBreak PRO HS Handle with 356mm Extension Shaft IP55 for B160/L160/B250/L250/ZS250 Grey



Item No: TPHS25SR5RM

Required: No

Description: Terasaki TemBreak PRO HS Handle with 356mm Extension Shaft IP55 for B160/L160/B250/L250/ZS250 Grey

Item No: XAB3

Required: No

Description: Terasaki TemBreak 1 Filler Pole suits X2 Models

