

P250H3250TM

Terasaki TemBreak PRO MCCB 250 Frame 70kA 3P 250A Adj.
Thermal Adj. Magnetic



Component type	Power switching circuit breaker
Range	TemBreak PRO
Model	N/A
Product status	Existing

The latest innovation of MCCBs from Terasaki, offering superior performance and versatility.



Rated current I_n	250.0 A
---------------------	---------

Number of poles	3.0
-----------------	-----

Max. rated operation voltage U_e AC	690.0 V
---------------------------------------	---------

Rated ultimate short-circuit breaking capacity I_{cu} at 415 V, 50 Hz	70.0 kA
---	---------

Rated service short-circuit breaking capacity I_{cs} at 415 V, 50 Hz	50.0 kA
--	---------

Type of protection trip unit	Thermal/magnetic release
------------------------------	--------------------------

Trip curve	Adj. thermal, adj. magnetic
------------	-----------------------------

Frame size rating	250.0 A
-------------------	---------

Long time overload protection adjustment range	160 - 250 A
--	-------------

Position of connection for main current circuit	Front side
---	------------

Instantaneous protection adjustment range	1500 - 2500 A
---	---------------

Rated frequency	50 - 60 Hz
-----------------	------------

Rated insulation voltage U_i	800.0 V
--------------------------------	---------

Suitable for isolation	Yes
------------------------	-----

Rated short circuit breaking capacity, I_{cu} 690V AC	6.0 kA
---	--------

Rated short circuit breaking capacity, I_{cs} 690V AC	6.0 kA
---	--------

Rated impulse withstand voltage U_{imp}	8.0 kV
---	--------

Over voltage category	IV
-----------------------	----

Reverse connection of supply possible	Yes
---------------------------------------	-----

AC power loss per pole at I_n	16.9 W
---------------------------------	--------

Electrical life at U_n , I_n (service cycles)	10000.0 cycles
---	----------------

Type of electrical connection of main circuit	Screw connection
---	------------------

Power loss at rated current	50.7 W
-----------------------------	--------

ELECTRICAL

P250H3250TM

Terasaki TemBreak PRO MCCB 250 Frame 70kA 3P 250A Adj.
Thermal Adj. Magnetic



MECHANICAL

Connectable conductor cross section	35 - 185 mm ²
Mechanical life (service cycles)	30000.0 cycles
Vibration acceleration (Max)	19.0 m/s ²
Vibration frequency, operational (Max)	16.7 Hz
Vibration duration (Max)	12.0 min

DIMENSIONS

Height	165.0 mm
Width	105.0 mm
Pole connection pitch	35.0 mm
Built-in depth	68.0 mm
Depth (toggle included)	95.5 mm
Weight	1.5 kg

ENVIRONMENT









Pollution degree	3.0
Rated surrounding temperature without derating	50.0 °C
Ambient temperature during operating	-5 - 70 °C
Max. temperature	70.0 °C
Storage temperature	-10 - 70 °C
Allowable relative humidity	0 - 85 %
Altitude before derating (Max)	2000.0 m

CERTIFICATES/APPROVALS

Standard	AS/NZS IEC 60947.2
----------	--------------------

RELATED PRODUCTS

ACCESSORY

	Item No: 2H6845CAA Required: No Description: Terasaki TemBreak 2 Plug In Kit 3P for E160/S160 to 250		Item No: 2H6959CDA Required: No Description: Terasaki TemBreak PRO Plug and Socket for Auxiliary/Alarm for Plug-in MCCB P400/P630
	Item No: 2H6959CAA1 Required: No Description: Terasaki TemBreak PRO Plug and Socket for Auxiliary/Alarm for Plug-in MCCB 250-800A		Item No: T2AL00LML3STA Required: No Description: Terasaki TemBreak PRO Alarm Switch for A and P Models 1 CO Contact Left Side Mounting General Type
	Item No: 2H6959CBA1 Required: No Description: Terasaki TemBreak PRO Plug and Socket for Shunt/UVT for Plug-in MCCB 250-800A		Item No: T2AL00LML3SWA Required: No Description: Terasaki TemBreak PRO Alarm Switch for A and P Models 1 CO Contact Left Side Mounting Wired Type
	Item No: 2H6959CCA Required: No Description: Terasaki TemBreak PRO Plug and Socket for Shunt/UVT for Plug-in MCCB P400/P630		Item No: T2AX00LML3RWA Required: No Description: Terasaki TemBreak PRO Auxiliary Switch for A and P Models 1 CO Contact Micro Switch Wired Type

P250H3250TM

Terasaki TemBreak PRO MCCB 250 Frame 70kA 3P 250A Adj.
Thermal Adj. Magnetic



RELATED PRODUCTS

ACCESSORY



Item No: T2AX00LML3STA

Required: No

Description: Terasaki TemBreak PRO Auxiliary Switch for A and P Models 1 CO Contact General Type

Item No: T2AX00LML3SWA

Required: No

Description: Terasaki TemBreak PRO Auxiliary Switch for A and P Models 1 NO Contact 1 NC Contact Wired Type

Item No: T2BA25L3SH

Required: No

Description: Terasaki TemBreak PRO Interpole Barriers for A250/P250/ZS250 Qty 2

Item No: T2CF161SLNG

Required: No

Description: Terasaki TemBreak 2 Terminal Cover Front Connect S160 1P MCCBs

Item No: T2CF25L3SLEP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Long Style with Barrier for 3P A250 and P250 MCCB Qty 2

Item No: T2CF25L3SLHP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Long Style for 3P A250 and P250 MCCB Qty 1

Item No: T2CF25L3SLNP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Long Style for 3P A250 and P250 MCCB Qty 2

Item No: T2CF25L3SSHP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Short Style for 3P A250 and P250 MCCB Qty 1

Item No: T2CF25L3SSNP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Short Style for 3P A250 and P250 MCCB Qty 2



Item No: T2CF25L3SWHP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Wide Style for 3P A250 and P250 MCCB Qty 1

Item No: T2CF25L3SWNP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Wide Style for 3P A250 and P250 MCCB Qty 2

Item No: T2CF25LL

Required: No

Description: Terasaki TemBreak PRO Terminal Cover Clip for A250/P250

Item No: T2CR25L3SHP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CR Flush Style for A250/P250 3P MCCB Qty 1

Item No: T2CR25L3SP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CR Flush Style for A250/P250 3P MCCB Qty 2

Item No: T2CS161SG

Required: No

Description: Terasaki TemBreak 2 Terminal Cover Flush for S160 1P MCCBs

Item No: T2CS25L3SP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CS Standard Style for A250/P250 3P MCCB Qty 2

Item No: T2DF25A


Required: No

Description: Terasaki TemBreak PRO Door Flange IP30 for B160/P250/B250 MCCB

Item No: T2FW25LS3A

Required: No

Description: Terasaki TemBreak PRO Tunnel Terminal fits 35 to 120mm² for A250/P250 Qty 6



P250H3250TM

Terasaki TemBreak PRO MCCB 250 Frame 70kA 3P 250A Adj.
Thermal Adj. Magnetic



RELATED PRODUCTS

ACCESSORY



Item No: T2HL25L

Required: No

Description: Terasaki TemBreak PRO Non Captive Toggle Lock 5 x 16.5mm Slot for A160/ A250/P160/P250



Item No: T2HS250SHAFT

Required: No

Description: Terasaki TemBreak 2 Handle Shaft 90mm for 125/250 MCCBs



Item No: T2HSESC100

Required: No

Description: Terasaki TemBreak 2 Handle Label Plate 100mm MCCBs



Item No: T2MM25L05A

Required: No

Description: Terasaki TemBreak PRO Motor Interlock Cable 0.5m for A/P/B/ZS MCCB Rated 12-250A



Item No: T2MM25L15A

Required: No

Description: Terasaki TemBreak PRO Motor Interlock Cable 1.5m for A/P/B/ZS MCCB Rated 12-250A



Item No: T2MM40S06A

Required: No

Description: Terasaki TemBreak PRO Motor Interlock Cable 0.6m for B250/ZS250 with 630 to 1000A MCCB



Item No: T2MM40S21A

Required: No

Description: Terasaki TemBreak PRO Motor Interlock Cable 2.1m for P160/P250 with 400 to 1000A MCCB



Item No: T2RP25L3SA

Required: No

Description: Terasaki TemBreak PRO Rear Connect Studs for 3P A250/P250 MCCB

Item No: T2SH00LA10WA

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 110-120V AC Wired Type



Item No: T2SH00LA20T

Required: No


Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 230-240V AC



Item No: T2SH00LA40T

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 400-415V AC



Item No: T2SH00LA40WA

Required: No


Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 380-450V AC Wired Type



Item No: T2SH00LD02T

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 24V DC



Item No: T2SH00LD02WA

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 24V DC Wired Type



Item No: T2SH00LD04WA

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 48V DC Wired Type



Item No: T2SH00LD20WA

Required: No



Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 200-240V DC Wired Type



Item No: T2TP003A

Required: No

Description: Terasaki TemBreak PRO Plug In Socket for Panel Mount



Item No: T2SH00LA10T

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 110V AC

P250H3250TM

Terasaki TemBreak PRO MCCB 250 Frame 70kA 3P 250A Adj.
Thermal Adj. Magnetic



RELATED PRODUCTS

ACCESSORY



Item No: T2UV00LA10NWA

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 100-120V AC Wired Type

Item No: T2UV00LA20NT

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 230 to 240V AC

Item No: T2UV00LA20NWA

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 200-240V AC Wired Type

Item No: T2UV00LA40NWA

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 380-450V AC Wired Type

Item No: T2UV00LD02NT

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 24V DC

Item No: T2UV00LD02NWA

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 24V DC Wired Type

Item No: T2UV00LD10NWA

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 100-120V DC Wired Type

Item No: T2UV00LD20NWA

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 200-240V DC Wired Type



Item No: TBPHP25PALK

Required: No

Description: Terasaki TemBreak PRO Mechanical Padlock Attachment for A160/A250 MCCB and Handle

Item No: TPCLCP25

Required: No

Description: Terasaki TemBreak PRO Captive Lock Cover for P250 Thermal Magnetic and Basic Electronic MCCB

Item No: TPFB163SBC

Required: No

Description: Terasaki TemBreak PRO Straight Extension Bars 3P P160 MCCB Qty 6



Item No: TPHB255UR5BN

Required: No

Description: Terasaki TemBreak PRO Handle Direct Mount with Door Interlock for P250 Black



Item No: TPHB255UR5RN

Required: No

Description: Terasaki TemBreak PRO Handle Direct Mount with Door Interlock for P250 Red



Item No: TPHP25SR6BN

Required: No

Description: Terasaki TemBreak PRO HP Handle with 421mm Extension Shaft IP65 for P250 Grey

Item No: TPHP25SR6RN

Required: No

Description: Terasaki TemBreak PRO HP Handle with 421mm Extension Shaft IP65 for P250 Red



Item No: TPHS25R5GM


Required: No

Description: Terasaki TemBreak PRO HS Handle with 356mm Extension Shaft IP55 for P250 MCCB Grey

Item No: TPHS25R5RM

Required: No

Description: Terasaki TemBreak PRO HS Handle with 356mm Extension Shaft IP55 for P250 MCCB Red



P250H3250TM

Terasaki TemBreak PRO MCCB 250 Frame 70kA 3P 250A Adj.
Thermal Adj. Magnetic



RELATED PRODUCTS

ACCESSORY



Item No: TPMC25SA10N

Required: No

Description: Terasaki TemBreak PRO Motor 110V AC for P160/P250



Item No: TPMC25SA24N

Required: No

Description: Terasaki TemBreak PRO Motor 230-240V AC for P160/P250



Item No: TPMC25SD02N

Required: No

Description: Terasaki TemBreak PRO Motor 24V DC for P160/P250



Item No: TPMC25SD04N

Required: No

Description: Terasaki TemBreak PRO Motor 48V DC for P160/P250



Item No: TPMC25SD10N

Required: No

Description: Terasaki TemBreak PRO Motor 110V DC for P160/P250



Item No: TPMC25SD20N

Required: No

Description: Terasaki TemBreak PRO Motor 220V DC for P160/P250



Item No: TPML25SL3

Required: No

Description: Terasaki TemBreak PRO Front Link Interlock Left Side Mount for 3P P250 MCCB



Item No: TPML25SL4

Required: No


Description: Terasaki TemBreak PRO Front Link Interlock Left Side Mount for 4P P250 MCCB



Item No: TPML25SR3

Required: No


Description: Terasaki TemBreak PRO Front Link Interlock Right Side Mount for P250 MCCB



Item No: TPMW00L

Required: No


Description: Terasaki TemBreak PRO Interlock Wire 1.5m for P Model MCCBs



Item No: TPMW00S

Required: No


Description: Terasaki TemBreak PRO Interlock Wire 1.0m for P Model MCCBs



Item No: TPMW25SCN

Required: No


Description: Terasaki TemBreak PRO Cable Interlock Kit without Wire for P250



Item No: TPPM25A3A

Required: No

Description: Terasaki TemBreak PRO Plug In Base 3P for P250 MCCB



Item No: TPSS00NA

Required: No

Description: Terasaki TemBreak PRO Smart Auxilliary Alarm Contact Switch