



PLUTO DIM 700 DC/NR


Australian approved dimmable constant current LED driver with selectable Power and CCT

Application

The perfect choice for constant current electronic lighting circuits

Design Specifications

- Compact design, SELV, electrical class II, EMC compliant
- Safe no load, overload, short circuit protection
- Onboard selectable output current (500/700mA)
- Onboard selectable colour temperature, suitable for SAL S9784 TC range - S9784/306/312/606 TC/DP
- Dimmable with a trailing edge dimmer, delivering flickerCONTROLLED driver performance
- Recommended SAL trailing edge dimmers SDD350UM, SDD400U, SDD350BT, SDA450U/LED



Performance

- Dimmable - **YES**
- Dimmer Type - **TRAILING EDGE**

Technical Specification

Product	Model No.	Input Voltage (V/AC)	Frequency (Hz)	Power Factor	Power (W)	Dimmable
	DIM700/28DC/NR	240	50	0.9	28	YES
Output Current (mA)			Dim (mm)			
700			180(L) x 45(W) x 30(H)			

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

THE SFI SYSTEM ELIMINATES LED FLICKERING.

**DIMMABLE
CONTROL WITH
SFI FLICKER
CONTROL
TECHNOLOGY**
when paired with
SAL SFI downlights



**DIM with
FLICKER
CONTROL**

For related
products
please
scan me

