


5 way lever push wire connector Biz'Wing 4 0.2-4 mm² (x 25)

Characteristics

Number of inputs : **5**
 Length (mm) : **29.8**
 Width (mm) : **20.64**
 Height (mm) : **9.6**

Norms

> EN 60998-1 ; EN
 60998-2-2

Benefits

- It is important to strip the wires up to 11 mm.
- Ergonomic, flexible levers ensure ease of use.
- For flexible and rigid wires up to 4 mm².
- Transparent body for better management of connections.

Compliance marks



GENERAL INFORMATION

Technical details

Permissible cross-section for flexible wires: 0.34 to 4 mm².
 Permissible cross-section for single and multi-stranded solid wires: 0.2 to 4 mm².
 Glow wire resistance: 850 °C.
 Maximum ambient operating temperature: 85 °C (T85).
 Voltage (V): 450.
 Current (A): 32.
 Strip off: 11 mm.
 Test points.
 Material: polycarbonate.

Instructions

1. Strip wires precisely up to 11 mm.
2. Do not twist multi-strand wires.
3. Open the levers.
4. Insert the stripped wires into the bottom of the connector.
5. Close the levers.

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 4.3
 Length (cm) : 10
 Depth (cm) : 8.6
 Net weight (kg) : 0.15
 Gross weight (kg) : 0.16



Outer package 1



Carton box

Height (cm) : 28.4
 Length (cm) : 45
 Depth (cm) : 23
 Net weight (kg) : 15
 Gross weight (kg) : 9.17



x 60.00

Outer package 2



Pallet

Height (cm) : 120
 Length (cm) : 80
 Depth (cm) : 130
 Net weight (kg) : 275.1
 Gross weight (kg) : 290.1



x 1800.00