

**3 way lever push wire connector Biz'Wing 4 0.2-4 mm<sup>2</sup> (x 50)**

**Characteristics**

Number of inputs : **3**  
 Length (mm) : **18.6**  
 Width (mm) : **20.64**  
 Height (mm) : **9.6**

**Norms**

> EN 60998-1 ; EN 60998-2-2

**Benefits**

- It is important to strip the wires up to 11 mm.
- Ergonomic, flexible levers ensure ease of use.
- For flexible and rigid wires up to 4 mm<sup>2</sup>.
- Transparent body for better management of connections.

**Compliance marks**



**GENERAL INFORMATION**

**Technical details**

Permissible cross-section for flexible wires: 0.34 to 4 mm<sup>2</sup>.  
 Permissible cross-section for single and multi-stranded solid wires: 0.2 to 4 mm<sup>2</sup>.  
 Glow wire resistance: 850 °C.  
 Maximum ambient operating temperature: 85 °C (T85).  
 Voltage (V): 450.  
 Current (A): 32.  
 Strip off: 11 mm.  
 Test points.  
 Material: polycarbonate.

**Instructions**

1. Strip wires precisely up to 11 mm.
2. Do not twist multi-strand wires.
3. Open the levers.
4. Insert the stripped wires into the bottom of the connector.
5. Close the levers.

**LOGISTIC INFORMATION**

**Packaging**



**Carton box**

Height (cm) : 4.3  
 Length (cm) : 10  
 Depth (cm) : 8.6  
 Net weight (kg) : 0.23  
 Gross weight (kg) : 0.24



**Outer package 1**



x 60.00

**Carton box**

Height (cm) : 28.4  
 Length (cm) : 45  
 Depth (cm) : 23  
 Net weight (kg) : 10.92  
 Gross weight (kg) : 10.97



**Outer package 2**



x 1800.00

**Pallet**

Height (cm) : 120  
 Length (cm) : 80  
 Depth (cm) : 130  
 Net weight (kg) : 329.1  
 Gross weight (kg) : 344.1

