

2 poles low current connectors for solid copper conductors Ø 0.4-0.9 mm (x 100)



Characteristics

Colour : **Orange**
 Number of inputs : **2**
 Maximum insulating Ø, all materials (mm) : **2.08**
 Quantity per box : **100**

Benefits

- Self-stripping.
- Moisture resistant.
- Transparent body.

GENERAL INFORMATION

Description

Self-stripping connectors for single stranded wires from Ø 0.4 to 0.9 mm (26-19 AWG).
 Maximum insulation diameter (mm): 2.08.
 Pre-filled with grease ensuring perfect resistance to moisture.

Technical details

Voltage (V): 10.
 Intensity (A): 8
 Dielectric strength (V): 2000.
 Insulation resistance > 10³ MΩ.
 Operating temperature (°C): -10 to +80.
 Humidity range: 0 to 95%.

Application(s)

Recommended in particular for telephony, alarm and surveillance systems, LED lighting, computer networks or home automation.

Instructions

1. Insert the wires (not stripped) into the connector and crimp with the BIZ 330 004 crimping tool for the best connection.

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 5.5
 Length (cm) : 5.5
 Depth (cm) : 5.5
 Net weight (kg) : 0.06
 Gross weight (kg) : 0.07



Outer package 1



Carton box

Height (cm) : 30
 Length (cm) : 29.5
 Depth (cm) : 24
 Net weight (kg) : 5.7
 Gross weight (kg) : 7



x 100.00

Outer package 2



Pallet

Height (cm) : 130
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 273.6
 Gross weight (kg) : 351



x 4800.00