

SG72911



Description

- High-quality miniature circuit breakers for commercial and residential applications
- Contact position indicator red - green
- Guide for secure terminal connection
- 3-position DIN rail clip, permits removal from existing busbar system
- Comprehensive range of accessories can be mounted subsequently
- Rated currents up to 63 A
- Tripping characteristics B, C, D
- Rated breaking capacity 6 kA according to IEC/EN 60898-1

SG28911



Rated current I_n (A)	Type Designation	Article No.	Units per package
6 kA, Characteristic C			
1-pole			
0.16	PLS6-C0.16	242662	12/120
0.25	PLS6-C0,25	242663	12/120
0.5	PLS6-C0,5	242665	12/120
0.75	PLS6-C0,75	242664	12/120
1	PLS6-C1	242666	12/120
1.5	PLS6-C1,5	242667	12/120
1.6	PLS6-C1,6	242668	12/120
2	PLS6-C2	242669	12/120
2.5	PLS6-C2,5	242670	12/120
3	PLS6-C3	242671	12/120
3.5	PLS6-C3,5	242672	12/120
4	PLS6-C4	242673	12/120
5	PLS6-C5	242674	12/120
6	PLS6-C6	242675	12/120
8	PLS6-C8	242676	12/120
10	PLS6-C10	242677	12/120
12	PLS6-C12	242678	12/120
13	PLS6-C13	242679	12/120
15	PLS6-C15	242680	12/120
16	PLS6-C16	242681	12/120
20	PLS6-C20	242682	12/120
25	PLS6-C25	242683	12/120
32	PLS6-C32	242684	12/120
40	PLS6-C40	242685	12/120
50	PLS6-C50	242686	12/120
63	PLS6-C63	242687	12/120

SG40111



1+N-pole 1.5MU			
0.16	PLS6-C0.16/1N	242728	8/80
0.25	PLS6-C0,25/1N	242729	8/80
0.5	PLS6-C0,5/1N	242731	8/80
0.75	PLS6-C0,75/1N	242730	8/80
1	PLS6-C1/1N	242732	8/80
1.5	PLS6-C1,5/1N	242733	8/80
1.6	PLS6-C1,6/1N	242734	8/80
2	PLS6-C2/1N	242735	8/80
2.5	PLS6-C2,5/1N	242736	8/80
3	PLS6-C3/1N	242737	8/80
3.5	PLS6-C3,5/1N	242738	8/80
4	PLS6-C4/1N	242739	8/80
5	PLS6-C5/1N	242740	8/80
6	PLS6-C6/1N	242741	8/80
8	PLS6-C8/1N	242742	8/80
10	PLS6-C10/1N	242743	8/80
12	PLS6-C12/1N	242744	8/80
13	PLS6-C13/1N	242745	8/80
15	PLS6-C15/1N	242746	8/80
16	PLS6-C16/1N	242747	8/80
20	PLS6-C20/1N	242748	8/80
25	PLS6-C25/1N	242749	8/80
32	PLS6-C32/1N	242750	8/80