

SG72911



## Description

- High-quality miniature circuit breakers for commercial and residential applications
- Contact position indicator red - green
- Guide for secure terminal connection
- 3-position DIN rail clip, permits removal from existing busbar system
- Comprehensive range of accessories can be mounted subsequently
- Rated currents up to 63 A
- Tripping characteristics B, C, D
- Rated breaking capacity 6 kA according to IEC/EN 60898-1

SG74311



Rated current $I_n$ (A)	Type Designation	Article No.	Units per package
<b>3-pole</b>			
0.16	PLS6-C0.16/3	242930	1/40
0.25	PLS6-C0,25/3	242931	1/40
0.5	PLS6-C0,5/3	242933	1/40
0.75	PLS6-C0,75/3	242932	1/40
1	PLS6-C1/3	242934	1/40
1.5	PLS6-C1,5/3	242935	1/40
1.6	PLS6-C1,6/3	242936	1/40
2	PLS6-C2/3	242937	1/40
2.5	PLS6-C2,5/3	242938	1/40
3	PLS6-C3/3	242939	1/40
3.5	PLS6-C3,5/3	242940	1/40
4	PLS6-C4/3	242941	1/40
5	PLS6-C5/3	242942	1/40
6	PLS6-C6/3	242943	1/40
8	PLS6-C8/3	242944	1/40
10	PLS6-C10/3	242945	1/40
12	PLS6-C12/3	242946	1/40
13	PLS6-C13/3	242947	1/40
15	PLS6-C15/3	242948	1/40
16	PLS6-C16/3	242949	1/40
20	PLS6-C20/3	242950	1/40
25	PLS6-C25/3	242951	1/40
32	PLS6-C32/3	242952	1/40
40	PLS6-C40/3	242953	1/40
50	PLS6-C50/3	242954	1/40
63	PLS6-C63/3	242955	1/40

SG73911



Rated current $I_n$ (A)	Type Designation	Article No.	Units per package
<b>3+N-pole</b>			
0.16	PLS6-C0.16/3N	242999	1/30
0.25	PLS6-C0,25/3N	243000	1/30
0.5	PLS6-C0,5/3N	243002	1/30
0.75	PLS6-C0,75/3N	243001	1/30
1	PLS6-C1/3N	243003	1/30
1.5	PLS6-C1,5/3N	243004	1/30
1.6	PLS6-C1,6/3N	243005	1/30
2	PLS6-C2/3N	243006	1/30
2.5	PLS6-C2,5/3N	243007	1/30
3	PLS6-C3/3N	243008	1/30
3.5	PLS6-C3,5/3N	243009	1/30
4	PLS6-C4/3N	243010	1/30
5	PLS6-C5/3N	243011	1/30
6	PLS6-C6/3N	243012	1/30
8	PLS6-C8/3N	243013	1/30
10	PLS6-C10/3N	243014	1/30
12	PLS6-C12/3N	243015	1/30
13	PLS6-C13/3N	243016	1/30
15	PLS6-C15/3N	243017	1/30
16	PLS6-C16/3N	243018	1/30
20	PLS6-C20/3N	243019	1/30
25	PLS6-C25/3N	243020	1/30
32	PLS6-C32/3N	243021	1/30
40	PLS6-C40/3N	243022	1/30
50	PLS6-C50/3N	243023	1/30
63	PLS6-C63/3N	243024	1/30