



## Main

Range	MAX9
Product brand	Clipsal
Product or component type	Enclosure
Device application	Distribution
Number of 18 mm modules per row	6
Provided equipment	Earthing bar Neutral bar Circuit identification label Blanking plate
Colour	White electric (RAL 9003)
Door type	Tinted transparent door - upwards

## Complementary

Enclosure mounting	Surface
Number of horizontal rows	1
[Ue] rated operational voltage	240/415 V AC
[In] rated current	100 A
[Ui] rated insulation voltage	500 V
Number of ways	6 ways
Cable entry	Knock-out cable entries
Type of rail	DIN
Enclosure material	Housing: plastic Front face: plastic
Width	142 mm
Height	210 mm
Depth	101 mm

## Environment

Standards	AS/NZS 61439-3 AS/NZS 3000
Fire resistance	650 °C
IP degree of protection	IP30
IK degree of protection	IK05

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	898.0 g
Package 1 Height	10.8 cm
Package 1 width	15.7 cm
Package 1 Length	21.7 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Weight	7.594 kg
Package 2 Height	21.0 cm

Package 2 width	34.8 cm
Package 2 Length	44.5 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>