


Product data sheet Characteristics

MX9B256P

Pin type comb busbar, MAX9, 2P, 100 A, 56 modules









Complementary

Number of ways	28 ways N + L
Poles configuration	28 x 2P
Connection pitch	18 mm
Insulation	Insulated
Device presentation	Cuttable
Provided components	10 end-pieces Tooth covers
[le] rated operational current	100 A
[Ue] rated operational voltage	230 V AC
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Mounting mode	Horizontal
Mounting location	Тор
Height	30 mm
Width	1017 mm
Depth	17 mm
Colour	Grey

Environment

Standards	AS/NZS 61439-3 AS/NZS 3000	
Fire resistance	960 °C	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	440 g	
Package 1 Height	1.7 cm	
Package 1 width	2.9 cm	
Package 1 Length	101.7 cm	
Unit Type of Package 2	CAR	

Number of Units in Package 2	10
Package 2 Weight	5 kg
Package 2 Height	9.5 cm
Package 2 width	10.5 cm
Package 2 Length	103 cm

Offer Sustainability

Green Premium product
☑ REACh Declaration
Yes
Compliant EEU RoHS Declaration
Yes
Yes
€Yes
China RoHS Declaration
Product Environmental Profile

Life Is On