

AT4122



ORDERING INFORMATION

| | |
|-------------|---|
| Order code | 13967 |
| Description | Microwave sensor 16m-internal kit - White |
| Item Code | AT4122 |

MECHANICAL

| | |
|-------------------|---------------|
| Body Material | Polycarbonate |
| Fitting Colour | White |
| Installation Type | Inbuilt |
| IP Rating | IP20 |

ELECTRICAL

| | |
|-----------------|-------|
| Input Frequency | 50 Hz |
| Input voltage | 230V~ |

DRIVER

| | |
|-------------|------------------------------------|
| Wiring Type | Re-wireable terminal block (4 pin) |
|-------------|------------------------------------|

SENSOR (S SUFFIX)

| | |
|---|---------|
| Adjustable Detection Area / Sensitivity | Yes |
| Adjustable Hold Time | Yes |
| Corridor Function | No |
| Detection Range | 16 m |
| Dusk Mode | Yes |
| Lux Adjustment | Yes |
| Lux Range | 0-50 lx |

| | |
|------------------------|------------|
| Manual Override | No |
| Sensor Type | Microwave |
| Switched Output | Yes |
| Switched Output Rating | 800 W |
| Time Delay | 5s - 30min |

COMPLIANCE

| | |
|-----------|---|
| Standards | AS/NZS 60669.1 AS/NZS 60669.2.1 AS CISPR 15 IEC 61000.3 AS/NZS 4268 |
|-----------|---|

WARRANTY

| | |
|-----------------------|-----------------------|
| Domestic Use Warranty | 3 RTB (Total 3 Years) |
|-----------------------|-----------------------|

DIMENSIONS

| | |
|----------------|-------|
| Product Height | 25 mm |
| Product Length | 70 mm |
| Product Width | 35 mm |