

## AT9208 RGBWW

LED STRIP KIT - IP54 - 4.8W/m - RGBWW

### Features

- Superior 24V design
- Weather resistant IP54
- Flexible, quality LED housing
- Includes 24V power supply
- D.I.Y. easy install
- Supplied with 3M adhesive tape



### MECHANICAL

<b>IP Rating</b>	IP54
------------------	------

### ELECTRICAL

<b>Electrical Rating</b>	Class II
--------------------------	----------

<b>Input Current</b>	0.5 A
----------------------	-------

<b>Input Frequency</b>	50 Hz
------------------------	-------

<b>Input voltage</b>	230Vac
----------------------	--------

In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%

<b>Maximum Wattage</b>	36 W
------------------------	------

<b>Watts Per Meter (W/m)</b>	4.8
------------------------------	-----

<b>Working Temp Range</b>	40 °C
---------------------------	-------

### LAMP

<b>CCT Configuration</b>	RGBW
--------------------------	------

<b>Lamp/LED voltage</b>	24 V
-------------------------	------

<b>LED's per meter</b>	60
------------------------	----

<b>Lumens /m</b>	210 lm/m
------------------	----------

### COLOUR TEMPERATURE

<b>LED Wattage</b>	24 W
--------------------	------

<b>System Lumens</b>	1050 lm
----------------------	---------

### DRIVER

<b>Driver Current</b>	1000 mA
-----------------------	---------

<b>Driver Included</b>	Yes
------------------------	-----

<b>Driver Mode</b>	Constant Current
--------------------	------------------

<b>Driver Power</b>	24 W
---------------------	------

<b>Driver Type</b>	Fixed output
--------------------	--------------

<b>Flex &amp; Plug or Lead Length</b>	1500 mm
---------------------------------------	---------

<b>Output voltage Range</b>	24
-----------------------------	----

<b>Wiring Type</b>	Re-wireable Flex & Plug (2 pin)
--------------------	---------------------------------

### WARRANTY

<b>Domestic Use Warranty</b>	3 (Yr) RTB
------------------------------	------------

### DIMENSIONS

<b>Cutting Interval</b>	200 mm
-------------------------	--------

<b>Product Height</b>	3 mm
-----------------------	------

<b>Product Length</b>	5000 mm
-----------------------	---------

<b>Maximum End to End Length</b>	5000 mm
----------------------------------	---------


<b>Product Width</b>	10 mm
----------------------	-------

## ORDERING INFORMATION

<b>Order code</b>	11507
<b>Description</b>	AT9208/RGBWW/KIT/5M~5 m 4.8W/m 24V LED STRIP KIT IP54 RGB+WW
<b>Driver Power</b>	24 W
<b>Item Code</b>	AT9208/RGBWW/KIT/5M

## LINE DRAWINGS

### AT9208/RGBWW



## Accessories

Order code	Item Code	Description
16678	<a href="#">AT9220/1M</a>	Square Shallow Extrusion KIT - 1M
16679	<a href="#">AT9220/2M</a>	Square Shallow Extrusion KIT - 2M
10173	<a href="#">AT9221/1M</a>	Square Deep Extrusion KIT - 1M
12057	<a href="#">AT9221/2M</a>	Square Deep Extrusion KIT - 2M
10163	<a href="#">AT9226/1M</a>	Square Corner Extrusion KIT - 1M
12208	<a href="#">AT9227/1M</a>	Triangular Corner Extrusion KIT - 1M
16685	<a href="#">AT9227/2M</a>	Triangular Corner Extrusion KIT - 2M
10520	<a href="#">AT9228/2M</a>	Square Deep Recessed Extrusion KIT - 2M
16681	<a href="#">AT9232/2M</a>	Square Shallow Recessed Extrusion KIT - 2M
16684	<a href="#">AT9235/2M</a>	Square Deep Extrusion KIT - 2M
16647	<a href="#">AT9260/RGB</a>	RGB RF Controller for LED Strip
16648	<a href="#">AT9261/RGB</a>	4-Channel Amplifier/Repeater for LED Strip

## Recommended Drivers

Order code	Item Code	Description
16647	<a href="#">AT9260/RGB</a>	RGB RF Controller for LED Strip

