



GIBRALTAR SL9722 TC - 15W


IP66 LED vandal proof batten, ceiling mount, 15 watt selectable CCT

Application


Multi-purpose commercial or industrial utility applications

Design Specifications

- Rounded, 92mm profile design, robust UV resistant, (dark grey) nylon construction
- Stainless steel secure fastening screws, IK10 protection
- Operating temperature -20 °C to +40°C
- Integral constant current non-dimmable LED driver, with selectable CCT 3000/4000/5700K
- Large terminal block for easy installation
- Opal polycarbonate diffuser



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CRI	CCT (K)
	SL9722/15TC	240	15	1500/1650/1650	80	3000/4000/5700

Beam Angle (°)	Body Colour	Dim (mm)
120	GREY	660(L) x 92(W) x 105(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

