





#### **UNITREK STR9017/15TC - 15W**

Unitrek single circuit, 15 watt single circuit track spot, with integral dimmable driver and selectable colour temperature

## **Application**

Ideal for decorative interior or residential designs

## **Design Specifications**

- Architectural cylindrical profile
- Robust Polyamide body profile, colour matt white or black
- High efficiency COB LED chip, CRI > 80, selectable colour temperature 3000/4000/5700K
- Multifaceted reflector system, polycarbonate lens, beam distribution 40 degree.
- 15 watt integral trailing edge dimmable driver, with an ON/OFF switch function conveniently located on the track adaptor.

#### **Performance**

- Dimmable YES
- Dimmer Type **Trailing edge**

























## **Technical Specification**

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	ССТ (К)	Body Colour
5	STR9017/15TC/WH	240	15	1000/1150/1100	3000/4000/5700	WHITE
-	STR9017/15TC/BK	240	15	1000/1150/1100	3000/4000/5700	BLACK
	STR9017/15RING/BK					BLACK RING INSERT
	STR9017/15RING/WH					WHITE RING INSERT






CRI	Beam Angle (°)	Dimmable	Dim (mm)
80	40	YES	70(W) x 140(H)
80	40	YES	70(W) x 140(H)
	40		
	40		

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".


### **Dimensions**



## **Photometric Data**

Unit: cd C0/C180\_\_\_\_\_ C90/C270\_\_\_\_\_

STR9017/15W/NDL at 5000K





# WHO NEEDS AN OLD TIMER CONTROL.

PIXIE SMART GPO IS SMARTER THAN THE REST. MULTIFUNCTION











For more information please scan me





