

DOWNLIGHTS

SLOGAN 3 LED CCT3 SELECTABLE SLIM



CONSTRUCTION:

- Low profile nylon housing with polycarbonate trim
- Polycarbonate Diffuser
- Spring steel retaining springs

FEATURES:


- Switch on the driver allowing selection between 3000K, 4000K and 6500K colour temperature
- Offers Thermal Insulation rating of IC-4
- High efficacy of 88-100Lm/W
- Complete with dimmable driver for selected leading and trailing edge dimmers (compatibility list on website)



| | R8WDLCT3-01 |
|---------------------------------|--------------------|
| Comparable to: | 50W halogen |
| Total Power (W): | 8.0/7.8/8.0 |
| Total light output (lm): | 720 / 780 / 700 |
| Efficacy (lm/cctW): | 90/101/88 |
| Lux at 1m (lux): | 250/280/250 |
| CCT (K): | 3000/4000/6500 |
| CRI: | 85 |
| Power Factor (PF): | 0.9 |
| Weight (kg) | 0.2 |

DIMENSIONS(mm) Diameter Cut-out Depth

| | | | |
|-------------|-----|-------|----|
| R8WDLCT3-01 | 114 | 90-95 | 29 |
|-------------|-----|-------|----|



ACCESSORIES

| | |
|--------------|--------------------------------|
| RLA350DTR-01 | LOADPRO 350W LED Rotary dimmer |
| RLA350DTT-01 | LOADPRO Touch Dimmer 250W |



Scan here for more product information