

## AT9208 White

LED STRIP KIT - IP54 - 4.8W/m - White

### Features

- Superior 24V design
- Weather resistant IP54
- Flexible, quality LED housing
- Includes 24V power supply
- D.I.Y. easy install
- Includes 3 strip connectors
- Supplied with 3M adhesive tape



### MECHANICAL

<b>IP Rating</b>	IP54
------------------	------

### ELECTRICAL

<b>Electrical Rating</b>	Class II
--------------------------	----------

#### Input Current

<b>AT9208/CW/KIT/10M</b> <b>AT9208/WW/KIT/10M</b>	0.6 A
--	-------

<b>AT9208/CW/KIT/5M</b> <b>AT9208/WW/KIT/5M</b>	0.5 A
--	-------

<b>Input Frequency</b>	50 Hz
------------------------	-------

<b>Input voltage</b>	230Vac
----------------------	--------

In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%

#### Maximum Wattage

<b>AT9208/CW/KIT/10M</b> <b>AT9208/WW/KIT/10M</b>	36 W
--	------

<b>AT9208/CW/KIT/5M</b> <b>AT9208/WW/KIT/5M</b>	24 W
--	------

#### Watts Per Meter (W/m)

<b>AT9208/CW/KIT/10M</b> <b>AT9208/WW/KIT/10M</b>	3.6
--	-----

<b>AT9208/CW/KIT/5M</b> <b>AT9208/WW/KIT/5M</b>	4.8
--	-----

<b>Working Temp Range</b>	40 °C
---------------------------	-------

### LAMP

<b>Macadam Steps (SDCM)</b>	5-step MacAdam Ellipse
-----------------------------	------------------------

<b>CCT Configuration</b>	Single
--------------------------	--------

<b>CRI</b>	>80
------------	-----

<b>Lamp/LED voltage</b>	24 V
-------------------------	------

<b>LED's per meter</b>	60
------------------------	----

#### Lumens /m

<b>AT9208/CW/KIT/10M</b>	288 lm/m
--------------------------	----------

<b>AT9208/CW/KIT/5M</b> <b>AT9208/WW/KIT/5M</b>	380 lm/m
--	----------

<b>AT9208/WW/KIT/10M</b>	270 lm/m
--------------------------	----------

### LED LIFETIME

<b>LED Lifetime</b>	>54000 hrs
---------------------	------------

This is the Reported LED Lifetime in Hours based on TM-21. Atom does not list the projected or calculated LED lifetime, which is normally longer as TM-21 Addendum B explicitly states " The Calculated and Projected Lp(DK) are not to be reported: This Lifetime refers to the life of a single LED however the system life is longer since the probability and binomial distribution of all LEDs in the system means that the average led is performing above the specification and compensates for the LEDs falling below.

<b>TM-21 Test Hours</b>	9000 hrs
-------------------------	----------

## COLOUR TEMPERATURE

CCT	
AT9208/CW/KIT/10M AT9208/CW/KIT/5M	4000 K
AT9208/WW/KIT/10M AT9208/WW/KIT/5M	3000 K
CCT Colour	
AT9208/CW/KIT/10M AT9208/CW/KIT/5M	Cool White
AT9208/WW/KIT/10M AT9208/WW/KIT/5M	Warm White
LED Wattage	
AT9208/CW/KIT/10M AT9208/WW/KIT/10M	36 W
AT9208/CW/KIT/5M AT9208/WW/KIT/5M	24 W
System Lumens	
AT9208/CW/KIT/10M	2880 lm
AT9208/CW/KIT/5M AT9208/WW/KIT/5M	1900 lm
AT9208/WW/KIT/10M	2700 lm

## DRIVER

Driver Current	
AT9208/CW/KIT/10M AT9208/WW/KIT/10M	1500 mA
AT9208/CW/KIT/5M AT9208/WW/KIT/5M	1000 mA
<b>Driver Included</b>	Yes
<b>Driver Mode</b>	Constant Current
Driver Power	
AT9208/CW/KIT/10M AT9208/WW/KIT/10M	36 W
AT9208/CW/KIT/5M AT9208/WW/KIT/5M	24 W
<b>Driver Type</b>	Fixed output
<b>Flex &amp; Plug or Lead Length</b>	1500 mm
<b>Output voltage Range</b>	24
<b>Wiring Type</b>	Re-wireable Flex & Plug (2 pin)

## WARRANTY

<b>Domestic Use Warranty</b>	3 (Yr) RTB
------------------------------	------------

## DIMENSIONS


<b>Cutting Interval</b>	100 mm
<b>Product Height</b>	3 mm
Product Length	
AT9208/CW/KIT/10M AT9208/WW/KIT/10M	10000 mm
AT9208/CW/KIT/5M AT9208/WW/KIT/5M	5000 mm
Maximum End to End Length	
AT9208/CW/KIT/10M AT9208/WW/KIT/10M	10000 mm
AT9208/CW/KIT/5M AT9208/WW/KIT/5M	5000 mm
<b>Product Width</b>	8 mm

## Ordering Information

Order code	Item Code	Description
11509	<b>AT9208/CW/KIT/10M</b>	10m 3.6W/m 24V LED STRIP KIT IP54 CW
11505	<b>AT9208/CW/KIT/5M</b>	5m 4.8W/m 24V LED STRIP KIT IP54 CW
11508	<b>AT9208/WW/KIT/10M</b>	10m 3.6W/m 24V LED STRIP KIT IP54 WW
11504	<b>AT9208/WW/KIT/5M</b>	5m 4.8W/m 24V LED STRIP KIT IP54 WW

## Line Drawings

### AT9208



## Accessories

Order code	Item Code	Description
16678	<b>AT9220/1M</b>	Square Shallow Extrusion KIT - 1M
16679	<b>AT9220/2M</b>	Square Shallow Extrusion KIT - 2M
10173	<b>AT9221/1M</b>	Square Deep Extrusion KIT - 1M
12057	<b>AT9221/2M</b>	Square Deep Extrusion KIT - 2M
10163	<b>AT9226/1M</b>	Square Corner Extrusion KIT - 1M
12208	<b>AT9227/1M</b>	Triangular Corner Extrusion KIT - 1M
16685	<b>AT9227/2M</b>	Triangular Corner Extrusion KIT - 2M
10520	<b>AT9228/2M</b>	Square Deep Recessed Extrusion KIT - 2M
16681	<b>AT9232/2M</b>	Square Shallow Recessed Extrusion KIT - 2M
16684	<b>AT9235/2M</b>	Square Deep Extrusion KIT - 2M
16648	<b>AT9261/RGB</b>	4-Channel Amplifier/Repeater for LED Strip